

healthcare

HTM64 (SK 2) doon double sink

SK 2 double bowl stainless steel sink in 2 depths, with earthing terminal.

- Domestic services sink assemblies
- Screw to wall, front legs or mounting on base unit versions
- Stainless steel
- 60cm & 65cm deep
- With tapholes as HTM64 (2006)

healthcare

HTM64



Illustrated

S5864 (SK 2) Doon double bowl sink and brackets, 120cm x 60cm, 2 tapholes at 20cm centres, no overflow, with earthing terminal
 S8265AA (TP3) Markwik 1/2in high neck pillar taps, inlets screwed 1/2in BSP male (2)
 S8768 (WT4) 1 1/2in waste, chain and plug with unslotted tail, screw stay (2)
 S8925 (TRR2/P) 1 1/2in plastic resealing bottle trap 75mm seal and multi-purpose outlet (2)

Finish

Exposed surfaces polished with 240 grain

Standards

Stainless steel sheet conforms to BS EN 10088.
 Conforms to HTM64 Sanitary Assemblies

Options

65cm deep
 S5866 Doon sink 120cm x 65cm, 2 tapholes at 20cm, for each bowl, no overflow
 S9272 stainless steel legs to floor (2 required)

Material

Stainless steel type 1.4301 (304)
 Bowl 0.9mm (before forming)
 Surround 1.2mm

Weight

Average weight 19.0kg

