

brassware markwik 21 thermostatic - sequential lever

Panel mounted bib mixer with integral thermostat, single long lever, horizontal single flow nozzle.

Sequential operation ensures both hot and cold water is drawn on each use, long lever gives precise control.

Designed for high and low pressure.

Insulated technology keeps the 'hot' side of the mixer at a safe surface temperature.

For use in medical and healthcare

Conforms to HTM64 (2006),
HTM04, HFN30

Front access for D 08 auditing &
servicing



Illustrated

A4553AA (TB H2a)
Markwik 21, integral
thermostat, single
sequential lever bib mixer,
single flow horizontal
outlet, 2 x 1/2in inlets

Weight

3.0kg

Options

S8239NU Markwik,
sterilisation kit
A4556AA Markwik,
purging tool (re-usable) for
insulate versions A4553,
A4554 & A4555

Special notes

Single lever operates
on/off and temperature
control.

Unique built-in sterilisation
cleansing feature, uses
one additional Sterilisation
kit S8239NU bridging
hose. Maintenance can
regularly flush through the
whole of any number of
taps with very hot water.

* Recommended height
over vessel.
Especially suited to
medium and large hospital
pattern integral back outlet
basins and washing
associated with clinical or
nursing procedures see
page 19:1:11M and
19:1:16B for typical TB
H2a use

