FM63 Gate Valve '%- (e e \$*-(e e \$+((e e

Materials


SEQUENCE	DESCRIPTION	MATERIAL	SIZES
1	Body Cast Iron	BSEN1561 GJL-250	All
2	Bonnet Cast Iron	BSEN1561 GJL-250	All
3	Bonnet Gasket	Asbestos Free	All
4	Bonnet Bolt Steel	BS4190 Gr.4.6	All
4	Bonnet Bolt Nut	Steel BS4190 Gr.4	All
5	Disc	Cast Iron BSEN1561 GJL-250	All
6	Stem	Brass ASTM B16-C36000 Half Hard	All
7	Stuffing Box	Cast Iron BSEN1561 GJL-250	All
8	Gland Flange	Ductile Cast Iron ASTM A536 Gr.65-45-12	All
9	Stuffing Box Stud	BS4439 Gr.4.8	200 - 300
9	Stuffing Box Stud N	BS4190 Gr.4	200 - 300
9	Gland Studs	BS4439 Gr.4.8	All
10	Stuffing Box Gasket	Asbestos Free	All
11	Packing	Asbestos Free	All
12	Handwheel	Malleable Iron BS EN 1562 GJMB-300-6	All
13	Washer	Steel	All
14	Body Seat Ring	Bronze BSEN1982 CC491K	All
15	Disc Stem Nut	Bronze BSEN1982 CC491K	All
16	Disc Ring	Bronze BSEN1982 CC491K	All
17	Handwheel Nut	BS4190 Gr.4	All
18	Gland Sud Nut	BS4190 Gr.4	All
19	Gland	Cast Iron BSEN1561 GJL-250	All



Dimensions and Weights

SIZE	WEIGHT (g)	A (mm)	B (mm)	C (mm)	D (mm)	E (mm)	F (mm)
50mm	17.9	178	20	165	288	178	102
250mm	194.5	330	32	405	773	406	319
300mm	275.5	356	32	460	860	457	370

Dimensional Drawing



Crane cast iron gate valves offer the ultimate in dependable service wherever minimum pressure drop is important. Each valve is hydrostatically tested to BS5150

PRESSURE RATING: PN16 UK END CONNECTION: Flanged BSEN1092-2

OPERATING INSTRUCTIONS: Handwheel. Gate valves are best for services that require infrequent valve operation, and where the disk is kept either fully opened or fully closed. They are not practical for throttling.

SPECIFICATION: Wedge Disk, Non-Rising Stem, Inside Screw.

This valve is not suitable for use on group 1 gasses or unstable fluids, as defined by the Pressure Equipment Directive 97/23/EC. Temperature operating range: - 10 to 200 degrees celsius.

AVAILABLE OPTIONS: Flanges undrilled, P50 locking device, P139 Stem Adapter, Extension Stem



CRANE HOUSE EPSILON TERRACE, WEST ROAD, IPSWICH SUFFOLK IP3 9FJ TELEPHONE: +44 (01473) 277300 FAX: +44 (01473) 277301 EMAIL: enquiries@cranebsu.com

www.cranefs.com

The Company reserve the right to amend any product without notice.

CFS_ 10.2010