

## AFTERCARE INSTRUCTIONS

Your fitting has a high quality finish and should be treated with care to preserve the visible surfaces. All surface finishes will wear if not cleaned correctly, the only safe way to clean your mixer is to wipe with a soft damp cloth. Stains can be removed using washing up liquid. All bath cleaning powders and liquids will damage the surface of your fitting even the non-scratch cleaners.

## GUARANTEE

All products are manufactured to the highest standards and a 5 year guarantee covers any defect in manufacture. As gold and special effect finishes are softer than chromium plate, special care must be taken when cleaning; a 3 year guarantee covers these.

**NOTE:** The 5 year guarantee on the valves is invalidated if damaged by any waterborne debris.

*In the interests of continuous product development we reserve the right to alter specification as necessary.*

**PRODUCT CODE: PM TBAS C / SAT / ST**

**TELEPHONE HELPLINE: 0844 701 6273**

Bristan Group Ltd  
Birch Coppice Business Park  
Dordon  
Tamworth  
Staffordshire  
B78 1SG  
UK  
A Masco Company

Web Site: [www.bristan.com](http://www.bristan.com)

Telephone: 0844 701 6273

Facsimile: 0844 701 6275

Email: [enquire@bristan.com](mailto:enquire@bristan.com)

# BRISTAN

## Prism Tall Basin Mixer

## Fitting Instructions & Contents List

**Please keep these instructions for future reference  
and for the ordering spare parts.**

(F1 PM TBAS)

(D4)

(ST)

For latest prices and delivery to your door visit MyTub Ltd 0845 303 8383 [www.mytub.co.uk](http://www.mytub.co.uk)



## WATER PRESSURE

This mixer is suitable for use at all supply pressures. However for optimum use both the hot and cold supplies should be reasonably balanced. If the fitting is installed at low pressure (tank fed), then the minimum distance from the outlet of the nozzle to the underside of the cold tank should be 1.8 metres to ensure adequate performance. This mixer should be installed in compliance with Water Regulations. Where the supplies are unbalanced, i.e. hot water from the cylinder tank / cold from the mains, approved check valves must be fitted in the supply pipes. For further details contact your Local Water Authority.

## INSTALLATION

1. Identify all components and check for completeness, particularly before arranging fitting.
2. Screw extension piece (7) onto the plinth (8)
3. Fit the mixer body (6) and extension tube (7) to the basin using the 'C' plate fixing kit (10 & 11). The full rubber washer (9) goes between the fitting and the basin, and the 'C' shaped rubber (10) and metal washers (11) on the underside of the basin, to be secured by the nut (12) and threaded rod (13).
4. Fit the flexible tails (14) to the fitting and connect the hot and cold supplies.
5. Fully open the mixer in the mid position, letting it run for a few minutes to check all joints and connections for leaks.
6. See over the page for aftercare instructions.

**Please Note:** In the unlikely event you find a part missing please contact our Customer Service Help line on 0844 701 6273 for immediate dispatch of part.

## MAINTANCE

### If the fitting begins to drip:

1. Isolate water supplies.
2. Prise out head cap (1), loosen grub screw (2) and lift off the head.
3. Unscrew the shroud (3) and brass retaining plate (4) and lift off the cartridge (5) complete with seal.
4. Clean or replace cartridge, clean and grease seal and refit.

**Note:** that there are locating pins on the bottom of the cartridge that fit in holes inside the tap, to ensure it is fitted the right way round.

5. Refit the head and tighten the grub screw. Replace the head cap.
6. If problem persists contact our helpline quoting the product code.

## CONTENTS

- |     |                    |      |
|-----|--------------------|------|
| 1.  | Head Cap           | (x1) |
| 2.  | Grub Screw         | (x1) |
| 3.  | Shroud             | (x1) |
| 4.  | Retaining Plate    | (x1) |
| 5.  | Cartridge          | (x1) |
| 6.  | Mixer Body         | (x1) |
| 7.  | Extension Piece    | (x1) |
| 8.  | Plinth             | (x1) |
| 9.  | Full Rubber Washer | (x1) |
| 10. | Rubber 'C' Washer  | (x1) |
| 11. | Metal 'C' Washer   | (x1) |
| 12. | Nut                | (x2) |
| 13. | Threaded Rod       | (x2) |
| 14. | Flexible Hose      | (x2) |

