



Plassone - The new range of innovative fittings created by Plasson, market leader in design and manufacture of reliable fittings for Polyethylene pipe systems.

push-fittings provide connectivity of Polyethylene (MDPE) pipe to a variety of plumbing pipe materials including MDPE, Copper, PB, and PEX. Inserting the pipe up to the fitting stop creates both the seal and the grip on the pipe.

Plassone is a WRAS approved 16 Bar rated fittings system for MDPE, PEX, PB and Copper, when used with an appropriate liner.

plumbing market, where space is limited and appearance is crucial. It is designed for the transition from MDPE pipe to Copper, PB and PEX within the building.

prassone is simple to assemble simply push to fit - makes both the professional's and occasional user's job easier whilst retaining the famous Plasson reliability.

The combination of Plasson's current fitting range and the new Plassone fulfill the requirements of all markets for MDPE pipe connections and connections to other pipe materials.

- Aesthetically designed product gives professional finish to the job
- Assembly tools not required simple push fit assembly
- Compact size can be assembled in confined spaces
- Instant seal and integrity of joint captive o-ring and no nuts to tighten
- Full end load performance no need to restrain joints
- Transition from MDPE to internal plumbing systems Copper, PB and PEX accommodated in one fitting
- Push fit assembly of Copper, PB and PEX similar to MDPE joint assembly
- 50 year design life provides total reliability
- Tamper resistant design ensures system integrity
- Packaged with liners for PE and full instructions for ease of handling
- Drip tight seal even at low or negative pressures
- Simply push to fit on Polyethylene, Copper, PEX and Polybutylene 'One push fits all.'



Email: sales@plasson.co.uk

Watertight Solutions

COUPLINGS	3
TEES & ADAPTORS	4
ELBOWS & END PLUGS	5
VALVES	6
METERING & STOP TAP CHAMBER	7-8
ACCESSORIES	9
ASSEMBLY INSTRUCTIONS	10-11
TECHNICAL DETAILS	12
CONTACT LIST	13

ALSO AVAILABLE



PLASSON®

Email: sales@plasson.co.uk







□ PLASSON®

- Compact and attractive plumbing fitting
- Push to fit on all pipes
- Adaptors from PE to Copper, PB, PEX and Imp. PE
- WRAS approved to 16 Bar
- Instant seal even at low or negative pressures
- Full end load performance
- Tamper resistant design for system integrity

Email: sales@plasson.co.uk www.plasson.co.uk





1011	Reducing Couplings
SIZE	PRICE (£) EACH
25x20	7.72
32x20 32x25	12.79 12.81

1001	Couplings
SIZE	PRICE (£) EACH
20x20	4.15
25x25	4.45
32x32	9.86
40x40	19.21
50x50	23.09
63x63	33.74





1001M	Imperial Coupling
SIZE	PRICE (£) EACH
20x ¹ / ₂	4.59
25x½	4.83
25x ³ / ₄	5.13
32x1	10.27

TOOTC	PE x Copper/PB/PEX
SIZE	PRICE (£) EACH
20x15	6.44
25x15 25x22	6.69 6.85
32x28	12.73

Fittings bagged individually. MDPE Liners included.

Metric to



Email: sales@plasson.co.uk www.plasson.co.uk



1004	Tees
SIZE	PRICE (£) EACH
20x20x20	6.76
25x25x25	10.65
32x32x32	14.52
40x40x40	24.83
50x50x50	30.34
63x63x63	45.63



1002C	Male Adaptor to Copper/PB/PEX
SIZE	PRICE (£) EACH
15x ³ / ₄ 22x ³ / ₄ 28x1	5.32 5.60 8.96



1002

	•		
SIZE	PRICE (£) EACH	SIZE	
20x ¹ / ₂	3.60	20x ¹ / ₂	
20x ³ / ₄	3.83	25x½	
25x ¹ / ₂	4.28	25x ³ / ₄	
25x ³ / ₄	4.28	25x1	
25x1	6.45	32x ³ / ₄	
32x ³ / ₄	6.62	32 x1	
32x1	6.62	32x11/4	
32x11/4	6.62	40x1	
40x1	12.06	40x1 ¹ / ₄	
40x1 ¹ / ₄	12.06	40x1½	
40x1½	12.06	50 x11/4	
50x1½	16.14	50 x1½	
50x2	16.14	50x2	
63x1½	21.68	63x1½	
63x2	21.68	63x2	




1003	Female Adaptors
SIZE	PRICE (£) EACH
20x1/2	4.13
25x½	4.69
25x ³ / ₄	4.52
25x1	5.80
32x ³ / ₄	5.97
32 x1	5.97
32x11/4	5.97
40x1	13.29
40x11/4	13.29
40x1½	13.29
50 x11/4	18.17
50 x1½	18.17
50x2	18.17
63x1½	26.16
63 x2	26.16

PLASSON® Email: sales@plasson.co.uk www.plasson.co.uk





1005	90° Elbows
SIZE	PRICE (£) EACH
20x20	4.99
25x25	7.09
32x32	11.56
40x40	20.92
50x50	24.60
63x63	32.70







1085	Male Elbows
SIZE	PRICE (£) EACH
20x½	3.50
20x ³ / ₄	3.50
25x½	4.03
25x ³ / ₄	4.03
25x1	4.03
32x ³ / ₄	6.74
32x1	6.74
32x11/4	6.74

1015	Female Elbows
SIZE	PRICE (£) EACH
20x1/2	4.53
20x3/4	4.53
25x1/2	5.92
25x ³ / ₄	5.92
25x1	5.92
32x ³ / ₄	9.57
32 x1	9.57
32x11/4	9.57

Fittings bagged individually. MDPE Liners included.

PLASSON

Email: sales@plasson.co.uk



0341	Stop Taps PRICE (£) EACH	
SIZE		
20x20	21.41	
25x25	30.12	
32x32	46.64	



0341C	PE x Copper/PB/PEX	
SIZE	PRICE (£) EACH	
20x15	26.66	
25x15	35.97	
25x22	37.50	
32x28	52.94	



	Bib Tap Hose Union with
9056a	Double Check Valve

7030u	Dooble Check valve
SIZE	PRICE (£) EACH
1/2"	20.66
3/4"	27.96



Bib Tap Hose Union with Double Check Valve

SIZE	PRICE (£) EACH
1/2"	15.50
3/4"	20.07



1000	Wall Plate Elbow	
SIZE	PRICE (£) EACH	
20x ¹ / ₂	9.12	
25x ¹ / ₂	9.71	
25x3/4	12.10	



2100	Bib Tap-Ball Type
SIZE	PRICE (£) EACH
1/2" 3/4"	7.35 13.13
74	13.13

E PLASSON®

Email: sales@plasson.co.uk

9056



Internal Meter Mounting Kit Copper/PB/PEX

SIZE	PRICE (£) EACH
25x22	64.20
25x15	64.20



3510	Water Meter Manifold
SIZE	PRICE
	(£) EACH

15 28.37

> For Copper Connection Only. Spare grip rings available.

Accessories

7002	Seal for Meter Plug
5177	0.76 Plug for Meter Mount
	1½"BSP 2.89



Concentric Water Meter 9001 (11/2" BSP)

PRICE (£) EACH SIZE

77.18



Stop Tap 3610 **Chamber Complete**

> 25.76 No Stop Tap included. Suits 20-32mm stop-tap. Load 1 Tonne Max. Plastic Lid.

3611 Tap Chamber Base		7.88
3612 Guard Tube	725mm	9.19
3613 Sleeve		3.94
3614 Surface Box		7.61

□ PLASSON®

Email: sales@plasson.co.uk







Manifolds & Manifold Kits

SIZE	DESCRIPTION	PRICE (£) EACH
3524004*Model 3530002	4-Port Centre Feed (2" BSP) Manifolds 4-Port Centre Feed Manifold Kit with Screw Down Valve	250.27 352.65
3524006 3530001*Model Shown	6-Port Centre Feed (2" BSP) Manifolds 6-Port Centre Feed Manifold Kit with Screw Down Valve	277.22 429.94
3523003 3530007	3-Port End Feed (2" BSP) Manifolds 3-Port End Feed Manifold Kit with Screw Down Valve	255.01 364.49
3523004*Model 3530006	4-Port End Feed (2" BSP) Manifolds 4-Port End Feed Manifold Kit with Screw Down Valve	292.50 438.47
3523006 3530005	6-Port End Feed (2" BSP) Manifolds 6-Port End Feed Manifold Kit with Screw Down Valve	329.98 548.94





DeadLeg Kit

SIZE	DESCRIPTION	PRICE
JIZL	DESCRIPTION .	(£) EACH
3534000	DeadLeg Kit for end feed Manifold only	37.76
3534001	DeadLeg Plug	32.41
3534002	DeadLeg Plug O Ring	1.60
5177	2" BSP Threaded Plug	4.54

EE PLASSON®

Email: sales@plasson.co.uk



SIZE PRICE (£) EACH 20 0.32 25 0.34 32 0.50 40 0.91 50 1.04 63 1.10	1095	Pipe Liner
25 0.34 32 0.50 40 0.91 50 1.04	SIZE	
32 0.50 40 0.91 50 1.04	20	0.32
40 0.91 50 1.04	25	0.34
50 1.04	32	0.50
	40	0.91
63 1.10	50	1.04
	63	1.10



1008C	Pipe Adaptor
SIZE	PRICE
mm	(£) EACH
15	0.15
22	0.25
28	0.50



60124	Valve Key
SIZE	PRICE (£) EACH
16mm Diame Universal key for	ter 33.95 T bar and square drive valves



7960	ChamferTool
SIZE	PRICE (£) EACH
20/63	57.44





F8030 400ml Aerosol Spray 15.54

F8029 30ml Tub



60125	Pipe Shears
SIZE	PRICE (£) EACH
20/32	30.08
60126	Pipe Shears
20/63	72.32 Replacement blades available



60123A	Pipe Squeeze off Tool
SIZE	PRICE
	(£) EACH
32/63	69.39



Email: sales@plasson.co.uk



(Connectable)
PRICE (£) EACH
0.34
0.37
0.42
0.76
0.84

MDPE Pipe Clips

PlassOne Fittings


Installation Instructions

Before installation, ensure that the end of the pipe to be inserted into the fitting is free of scratches and other imperfections and that both the pipe and the fitting itself are free of sand, mud, stones, etc. If fittings are reused, ensure that split ring and grip ring teeth are sharp and bite into the pipe, to avoid pullouts. If uncertain, replace the split ring and grip ring.


We strongly recommend the use of PTFE tape in threaded connections.

For diameters 40mm and above, chamfering and lubrication of the pipe end will ease insertion (use silicone lubricant).


When using PEX/PB pipes, use pipe manufacturers liner (see page11, fig 5).



Disassembly - PE x PE



Disassembly - PE x Copper/PB/PEX (PB illustrated)





MATERIALS

Compression Fittings:

Bodies and nuts in Polypropylene O-Rings in Nitrile Rubber (NBR) Reinforcing rings and toothed grips are in Stainless Steel.

Valves:

Bodies and nuts in Propropylene Split rings in White Polyacetal

Operating Temperatures:

Not suitable for hot water, however, will withstand sub zero temperature.

Threads:

Internal parallel thread External taper thread

All threads conform to:-ISO 7 BS 21-1973 DIN 2999 NEN 3258 AS 1722 / Part 1 - 1975.

Chemical Resistance:

Plasson fittings are supplied, as standard, with Polyacetal split rings and NBR O-rings which are suitable for water.

Operating Pressures and Quality Certificates:

Plasson Fittings are tested and approved by WRAS in the UK to PN 16.


Plasson have established a quality assurance system and achieved recognition under the Quality Standard ISO 9001:2000.

Operation in accordance with ISO 9001:2000 Quality Assurance system imposes stringent standards of control throughout the manufacturing process and selection of raw materials.

PLASSON

Email: sales@plasson.co.uk

EE PLASSONWatertight Solutions



Simon Merckel

Sales & Marketing Manager Email: simon.merckel@plasson.co.uk Mobile: 07788 185678

Duncan Fisher

Technical Support Manager Email: duncan.fisher@plasson.co.uk Mobile: 07788 185674

□ PLASSON®

Email: sales@plasson.co.uk

Rep. of Ireland / N. Ireland

Tel: 01444 244446 Fax: 01444 258683

