Polypipe Plumbing & Heating

Trade Price List 2013

© **Polypipe**

Contents

Plumbing & Heating
Trade Price List 2013

Welcome to the new Polypipe Plumbing and Heating Systems Trade Price List. This handy pocket guide combines all of our plumbing and heating related products into one single catalogue of product and price information. Alongside all of our best known product ranges, you will also find several exciting new additions, continuing our reputation for product innovation and great value. Together they make Polypipe the most comprehensive range of plumbing and heating systems available for a single UK manufacturer.

Be sure to check out these great new products:

For the latest product and support information, literature downloads, product selectors and news visit us online at **www.polypipe.com/plumbing-heating**

Plumbing

Heating

Underfloor Heating System

Plumbing & Heating Applications

PIPE SYSTEMS

(For Plumbing, Heating and Underfloor Heating)

FITTING SYSTEMS

(For Plumbing and Heating)

UNDERFLOOR HEATING SYSTEMS

MANIFOLDS & WATER TEMPERATURE CONTROL

(Underfloor and Central Heating System)

ROOM TEMPERATURE CONTROLS

(Underfloor and Central Heating System)

Plumbing & Heating Pipes

At the heart of the Polypipe Plumbing and Heating Systems product offer is our commitment to polybutylene pipe.

We choose polybutylene to create the most flexible and efficient pipes and jointing systems available. Polybutylene pipe is ideal for both domestic hot and cold water plumbing and heating systems, offering exceptional durability and long-term performance, which has seen it become the preferred material choice for today's building projects.

The most important characteristic of polybutylene is its natural flexibility, allowing you to bend the pipe into even the tightest of spaces. Polybutylene is the most malleable plastic used in the manufacture of piping systems.

Another key advantage of polybutylene pipe is that it is extremely lightweight, particularly when compared with copper piping systems. For example, 15mm copper tube will weigh approximately 0.28kg/m, compared to just 0.074kg/m for polybutylene. This significant weight reduction is invaluable when transporting materials to site.

Polybutylene pipe has good resistance to freezing temperatures, maintaining long-term durability in heating and water applications. This, combined with the pipe's elasticity, means that if water is subjected to freezing temperatures, a burst pipe is less likely.

Our plumbing systems also give improved performance over rigid pipe systems in terms of low noise transmission and low water hammer effect.

Underfloor heating pipe systems

We have supplemented our pipe offers with two ranges of underfloor specific pipe. Our ultra flexible underfloor heating pipe aids installation and handleability whilst our formable MCP pipes provide alternative for installers familiar with this pipe characteristic.

Polypipe Grey Plumbing, Heating and Underfloor Heating Pipe - BS 7291 Class S

Barrier Polybutylene Pipe Cut Length (Grey)	Pack Qty.	Code No.	Price Each £
15mm x 3 metre Barrier	10	PB315B	6.29
15mm x 6 metre Barrier	10	PB615B	12.33
22mm x 3 metre Barrier	10	PB322B	11.93
22mm x 6 metre Barrier	10	PB622B	22.99
28mm x 3 metre Barrier	10	PB328B	17.63
28mm x 6 metre Barrier	10	PB628B	35.05

Barrier Polybutylene Pipe Coil (Grey)	Pack Qty.	Code No.	Price Each £
10mm x 50 metre Barrier	1	PB5010B	86.81
10mm x 100 metre Barrier	1	PB10010B	167.14
15mm x 25 metre Barrier	1	PB2515B	49.84
15mm x 50 metre Barrier	1	PB5015B	99.68
15mm x 80 metre Barrier	1	PB8015B	155.76
15mm x 100 metre Barrier	1	PB10015B	198.19
15mm x 120 metre Barrier	1	PB12015B	230.64
15mm x 150 metre Barrier	1	PB15015B	297.00
22mm x 25 metre Barrier	1	PB2522B	97.23
22mm x 50 metre Barrier	1	PB5022B	188.82
28mm x 25 metre Barrier	1	PB2528B	108.52
28mm x 50 metre Barrier	1	PB5028B	214.66

Standard Polybutylene Pipe Cut Length (Grey)	Pack Qty.	Code No.	Price Each £
15mm x 3 metre Standard	10	PB315	5.45
15mm x 6 metre Standard	10	PB615	10.98
22mm x 3 metre Standard	10	PB322	10.32
22mm x 6 metre Standard	10	PB622	20.73
28mm x 3 metre Standard	10	PB328	14.20
28mm x 6 metre Standard	10	PB628	28.33

Standard Polybutylene Pipe Coil (Grey)	Pack Qty.	Code No.	Price Each £
10mm x 50 metre Standard	1	PB5010	75.80
10mm x 100 metre Standard	1	PB10010	153.83
15mm x 25 metre Standard	1	PB2515	45.09
15mm x 50 metre Standard	1	PB5015	89.58
15mm x 100 metre Standard	1	PB10015	179.01
22mm x 25 metre Standard	1	PB2522	85.31
22mm x 50 metre Standard	1	PB5022	169.68

Polypipe White Plumbing, Heating and Underflow Heating Pipe - BS 7291 Class S

Barrier Polybutylene Pipe Cut Length (White)	Pack Qty.	Code No.	Price Each £
15mm x 2 metre Barrier	10	FIT215B	4.27
15mm x 3 metre Barrier	10	FIT315B	6.29
15mm x 6 metre Barrier	10	FIT615B	12.33
22mm x 2 metre Barrier	10	FIT222B	8.20
22mm x 3 metre Barrier	10	FIT322B	11.93
22mm x 6 metre Barrier	10	FIT622B	22.99
28mm x 3 metre Barrier	10	FIT328B	17.63
28mm x 6 metre Barrier	10	FIT628B	35.05

Barrier Polybutylene Pipe Coil (White)	Pack Qty.	Code No.	Price Each £
10mm x 25 metre Barrier	1	FIT2510B	41.78
10mm x 50 metre Barrier	1	FIT5010B	86.81
10mm x 100 metre Barrier	1	FIT10010B	167.14
15mm x 25 metre Barrier	1	FIT2515B	49.84
15mm x 50 metre Barrier	1	FIT5015B	99.68
15mm x 100 metre Barrier	1	FIT10015B	198.19
15mm x 120 metre Barrier	1	FIT12015B	237.81
15mm x 150 metre Barrier	1	FIT15015B	297.00
22mm x 25 metre Barrier	1	FIT2522B	97.23
22mm x 50 metre Barrier	1	FIT5022B	188.82
28mm x 25 metre Barrier	1	FIT2528B	108.52
28mm x 50 metre Barrier	1	FIT5028B	214.66

Polypipe Grey Plumbing, Heating and Underfloor Heating Pipe - BS 7291 Class S

Barrier Polybutylene Pipe Coil (Grey)	Pack Qty.	Code No.	Price Each £
15mm x 50 metre Barrier	1	PB5015B	99.68
15mm x 80 metre Barrier	1	PB8015B	155.76
15mm x 100 metre Barrier	1	PB10015B	198.19
15mm x 120 metre Barrier	1	PB12015B	230.64
15mm x 150 metre Barrier	1	PB15015B	297.00

Polypipe Ultra Flexible Underfloor Heating Pipe (For Underfloor Heating Use Only) - EN15876

Underfloor Heating Pipe Polybutylene	Pack Qty.	Code No.	Price Each £
12mm x 25m Coil UFH Pipe	1	UFH2512B	35.50
12mm x 50m Coil UFH Pipe	1	UFH5012B	71.00
12mm x 80m Coil UFH Pipe	1	UFH8012B	113.60
15mm x 50m Coil UFH Pipe	1	UFH5015B	81.00
15mm x 80m Coil UFH Pipe	1	UFH8015B	129.60
15mm x 100m Coil UFH Pipe	1	UFH10015B	162.00
15mm x 120m Coil UFH Pipe	1	UFH12015B	194.40
15mm x 150m Coil UFH Pipe	1	UFH15015B	243.00
18mm x 120m Coil UFH Pipe	1	UFH12018B	252.00
18mm x 200m Coil UFH Pipe	1	UFH20018B	420.00
18mm x 300m Coil UFH Pipe	1	UFH30018B	630.00

NEW

Polypipe MCP Underfloor Heating Pipe
(For Underfloor Heating Use Only) - EN21003

Metal Composite Pipe	Pack Qty.	Code No.	Price Each £	
16mm x 80m Coil MCP UFH Pipe	1	MCP8016B	156.80	
16mm x 100m Coil MCP UFH Pipe	1	MCP10016B	196.00	
16mm x 120m Coil MCP UFH Pipe	1	MCP12016B	235.20	
16mm x 150m Coil MCP UFH Pipe	1	MCP15016B	294.00	

Pipe in Pipe and Conduit Pipe

Barrier Pipe-in-Pipe Coil (Grey)	Pack Qty.	Code No.	Price Each £	
10mm x 50 metre Pipe in Pipe	1	PIP5010B	154.30	
15mm x 25 metre Pipe in Pipe	1	PIP2515B	84.22	
15mm x 50 metre Pipe in Pipe	1	PIP5015B	168.64	
22mm x 25 metre Pipe in Pipe	1	PIP2522B	144.23	

Conduit Polypropylene Pipe Coil	Pack Qty.	Code No.	Price Each £	
15mm x 25 metre (Black)	1	CPC1525	27.30	
15mm x 50 metre (Black)	1	CPC1550	54.91	
22mm x 25 metre (Black)	1	CPC2225	34.11	
22mm x 50 metre (Black)	1	CPC2250	68.61	
15mm x 25 metre (Red)	1	CPC1525R	29.49	
15mm x 50 metre (Red)	1	CPC1550R	59.29	
22mm x 25 metre (Red)	1	CPC2225R	39.55	
22mm x 50 metre (Red)	1	CPC2250R	79.58	
15mm x 25 metre (Blue)	1	CPC1525BU	29.49	
15mm x 50 metre (Blue)	1	CPC1550BU	59.29	
22mm x 25 metre (Blue)	1	CPC2225BU	39.55	
22mm x 50 metre (Blue)	1	CPC2250BU	79.58	

Plumbing & Heating Fittings

Polypipe recognises that no two jobs are the same and has developed an application-based range of plumbing solutions with four fittings ranges, backed by a range of pipe options.

Plumbing fitting ranges:

PolyPlumb Traditional push fit plumbing

Original robust, grey system, suitable for a range of applications

PolyMax Streamline push fit plumbing

Slim and sleek, ideal for surface mounted applications

PolyFit Quickfix push fit plumbing

Hand demountable, ideal for first fix applications

PolySure Permanent press fit plumbing

Slim profile fittings, ideal when security is paramount

Each range is available in a wide selection of fitting types plus valves, connectors, brassware and accessories. Combine with the appropriate selection from our comprehensive range of piping systems.

Find out more about Polypipe plumbing at **www.polypipe.com/plumbing-heating**

Poly**Plumb**

Traditional push fit plumbing

PolyPlumb is our original, tried and tested, grey plumbing system. Robust and reliable, PolyPlumb has stood the test of time.

PolyPlumb fittings feature a one step jointing process and a high performance stainless steel grab ring within the fitting, ensuring superb joint integrity. Use PolyPlumb with Polypipe grey polybutylene flexible pipe, or you can combine PolyPlumb fittings and copper pipe. We recommend the use of a Polypipe metal or plastic pipe stiffener when used with plastic pipe.

PolyPlumb is suitable for use in most plumbing and heating installations including hot and cold water and underfloor heating applications.

Straight Coupler	Pack Qty.	Code No.	Price Each £
10mm	10	PB010	3.25
15mm	10	PB015	2.01
22mm	10	PB022	2.67
28mm	5	PB028	7.68

Socket Reducer	Pack Qty.	Code No.	Price Each £
15mm x 10mm	10	PB1815	3.10
22mm x 15mm (not suitable for use with compression fittings)	10	PB1822	2.42
28mm x 22mm (not suitable for use with compression fittings)	5	PB1828	5.51

Spigot Reducer	Pack Qty.	Code No.	Price Each £
15mm x 10mm	5	PB815	1.68
22mm x 15mm (22mm end not suitable for use with compression fittings)	5	PB822	1.86
28mm x 22mm (not suitable for use with compression fittings)	5	PB828	3.51

Reducing Coupling	Pack Qty.	Code No.	Price Each £
22mm x 10mm	5	PB582210	4.90

Elbow	Pack Qty.	Code No.	Price Each £
10mm	10	PB110	3.59
15mm	10	PB115	2.35
22mm	10	PB122	3.46
28mm	5	PB128	8.20

Spigot Elbow	Pack Qty.	Code No.	Price Each £
10mm	10	PB1010	3.74
10mm x 15mm	10	PB101510	3.42
15mm	10	PB1015	2.61
22mm (not suitable for use with compression fittings)	10	PB1022	3.88

Equal Tee	Pack Qty.	Code No.	Price Each £
10mm	10	PB210	4.50
15mm	10	PB215	3.39
22mm	10	PB222	4.43
28mm	5	PB228	13.04

Plumbing & Heating Fittings

PolyPlumb

End Reduced Tee	Pack Qty.	Code No.	Price Each £
15mm x 10mm x 15mm	5	PB1415	**4.49**
22mm x 15mm x 22mm	5	PB1422	**4.55**
28mm x 22mm x 28mm	5	PB1428	**13.04**

Branch Reduced Tee	Pack Qty.	Code No.	Price Each £
15mm x 15mm x 10mm	5	PB1115	**4.62**
22mm x 22mm x 10mm	5	PB112210	**4.63**
22mm x 22mm x 15mm	5	PB1122	**4.52**
28mm x 28mm x 22mm	5	PB1128	**11.59**

Two Ends Reduced Tee	Pack Qty.	Code No.	Price Each £
15mm x 15mm x 22mm	5	PB1622	**4.49**

Branch and One End Reduced Tee	Pack Qty.	Code No.	Price Each £
15mm x 10mm x 10mm	5	PB1515	**4.30**
22mm x 15mm x 15mm	5	PB1522	**4.41**
28mm x 22mm x 22mm	5	PB1528	**11.59**

Branch Reduced Spigot Tee	Pack Qty.	Code No.	Price Each £
15mm x 15mm x 10mm	5	PB1215	**4.49**
22mm x 22mm x 15mm (not suitable for use with compression fittings)	5	PB1222	**4.60**

Spigot Blank Ends	Pack Qty.	Code No.	Price Each £
10mm	10	PB910	**1.02**
15mm	10	PB915	**0.80**
22mm (not suitable for use with compression fittings)	10	PB922	**1.05**
28mm (not suitable for use with compression fittings)	5	PB928	**1.90**

Socket Blank Ends	Pack Qty.	Code No.	Price Each £
10mm	10	PB1910	**1.98**
15mm	10	PB1915	**1.58**
22mm	10	PB1922	**2.28**
28mm	5	PB1928	**3.83**

Demountable Socket Blank Ends	Pack Qty.	Code No.	Price Each £
10mm	10	PB6910	1.98
15mm	10	PB6915	1.59
22mm	10	PB6922	2.28
28mm	5	PB6928	3.83

Straight Tap Connector (Brass Connecting Nut)	Pack Qty.	Code No.	Price Each £
15mm x 1/2″ (1)	10	PB715	3.43
15mm x 3/4″ (2)	5	PB71534	4.98
22mm x 3/4″ (2)	5	PB722	5.42

(1) Complete with E.P.D.M. Sealing Washer. Spare flat seal included
    (tighten by hand plus a further 1/4 of a turn with a spanner)
(2) Complete with fibre sealing washer
    (tighten by hand plus a further 1/6 of a turn with a spanner)

Hand Tighten Tap Connector (Not suitable for central heating)	Pack Qty.	Code No.	Price Each £
15mm x 1/2″	10	PB2715	2.75
15mm x 3/4″	5	PB271534	3.28
22mm x 3/4″	5	PB2722	3.68

Complete with E.P.D.M. Sealing Washer

Bent Tap Connector (Brass Connecting Nut)	Pack Qty.	Code No.	Price Each £
15mm x 1/2″	10	PB1715	5.78

Complete with E.P.D.M. Sealing Washer. Spare flat seal included
(tighten by hand plus a further 1/4 of a turn with a spanner)

Flexible Hose Tap Connector (Not suitable for central heating)	Pack Qty.	Code No.	Price Each £
10mm x 1/2″	2	PB681012	10.62
15mm x 1/2″	2	PB6815	7.46
15mm x 3/4″	2	PB681534	8.76
22mm x 3/4″	2	PB6822	8.05

Tank Connector (Cold water only)	Pack Qty.	Code No.	Price Each £
15mm x 1/2″	10	PB3815	2.64
22mm x 3/4″	10	PB3822	3.47
28mm x 1″	5	PB3828	8.33

Complete with E.P.D.M. Sealing Washer (tighten by hand)

Wall Plate Elbow (Cold water only) (Use PTFE tape to seal threads)	Pack Qty.	Code No.	Price Each £
15mm x 1/2″	5	PB5315	5.40
22mm x 1/2″	5	PB532212	5.94
22mm x 3/4″	5	PB5322	6.71

PolyPlumb

Wall Plate Elbow (Brass) (Use PTFE tape to seal threads)	Pack Qty.	Code No.	Price Each £	
15mm x 1/2"	5	PB1315	**16.28**	
22mm x 1/2"	5	PB132212	**18.02**	
28mm x 1/2"	5	PB132812	**33.77**	

Wall Plate Tee (Brass) (Use PTFE tape to seal threads)	Pack Qty.	Code No.	Price Each £	
15mm x 1/2"	5	PB5115	**18.02**	
22mm x 1/2"	5	PB512212	**19.66**	

Female Elbow (Brass) (Use PTFE tape to seal threads)	Pack Qty.	Code No.	Price Each £	
15mm x 1/2"	5	PB3015	**8.64**	
22mm x 1/2"	5	PB302212	**9.33**	
22mm x 3/4"	5	PB3022	**9.33**	

Female Tee (Brass) (Use PTFE tape to seal threads)	Pack Qty.	Code No.	Price Each £	
15mm x 1/2"	5	PB2915	**12.58**	
22mm x 1/2"	5	PB292212	**14.29**	

Conduit Terminal Box	Pack Qty.	Code No.	Price Each £	
Includes 15mm x 1/2" Wall Plate Elbow	2	PB4515	**9.66**	

Polybutylene Double Sided Manifold (Grey) (Use Ball Valve to convert to Valved Manifold)	Pack Qty.	Code No.	Price Each £	
22mm x 10mm - 2 Port (Socket/Socket)	5	PB2822	**10.52**	
22mm x 10mm - 4 Port (Socket/Socket)	5	PB4822	**12.41**	
22mm x 10mm - 4 Port (Socket/Spigot)	5	PB4922	**12.41**	

Polybutylene Single Sided Manifold (Grey) (Use Ball Valve to convert to Valved Manifold)	Pack Qty.	Code No.	Price Each £	
22mm x 15mm - 3 Port (Socket/Socket)	1	PB7322153	**8.32**	
22mm x 15mm - 3 Port (Socket/Spigot)	1	PB7622153	**8.51**	
22mm x 10mm - 4 Port (Socket/Socket)	1	PB7322104	**12.27**	
22mm x 10mm - 4 Port (Socket/Spigot)	1	PB7622104	**12.27**	

Brass Single Sided Manifold Unvalved (Brass) (Use PTFE tape to seal threads)	Pack Qty.	Code No.	Price Each £
15mm x 3/4" Female/Male BSP 2 Port	1	PB47152	20.25
15mm x 3/4" Female/Male BSP 3 Port	1	PB47153	32.53

Brass Single Sided Manifold Valved (Brass) (Use PTFE tape to seal threads)	Pack Qty.	Code No.	Price Each £
15mm x 3/4" Female/Male BSP 2 Port	1	PB5234152	42.29
15mm x 3/4" Female/Male BSP 3 Port	1	PB5234153	64.82

Manifold Bracket (Metal)	Pack Qty.	Code No.	Price Each £
3/4"	2	PB4634	9.21

Stopcock (Grey) (Cold water only)	Pack Qty.	Code No.	Price Each £
15mm x 15mm	5	PB2615	8.74
22mm x 22mm	5	PB2622	10.46

MDPE Stopcock (Grey) (Polyfast) (Cold water only)	Pack Qty.	Code No.	Price Each £
20mm MDPE x 15mm	5	PB262015	16.06
25mm MDPE x 15mm	5	PB262515	13.22
25mm MDPE x 22mm	5	PB262522	16.84

Gate Valve (Brass)	Pack Qty.	Code No.	Price Each £
15mm	5	PB3115	15.27
22mm	5	PB3122	21.47

Shut-Off Valve (White) (Not suitable for central heating)	Pack Qty.	Code No.	Price Each £
15mm x 15mm Warm/Cold (Please note these valves now contain a plain white index)	5	PB5915	5.77

Appliance Valve (White) (Not suitable for central heating)	Pack Qty.	Code No.	Price Each £
15mm x 3/4" Warm/Cold (Please note these valves now contain a plain white index)	5	PB6115	5.76

PolyPlumb

Straight Service Valve (White) (Not suitable for central heating)	Pack Qty.	Code No.	Price Each £	
15mm x 1/2"	5	PB6515	**8.46**	

Bent Service Valve (White) (Not suitable for central heating)	Pack Qty.	Code No.	Price Each £	
15mm x 1/2" 90°	5	PB6615	**9.18**	

Bent Service Valve (White) (Not suitable for central heating)	Pack Qty.	Code No.	Price Each £	
15mm x 15mm 90° (Please note these valves now contain a plain white index)	5	PB7915	**9.18**	

Double Check Valve (Not suitable for central heating)	Pack Qty.	Code No.	Price Each £	
15mm	1	PB3715	**20.54**	
22mm	1	PB3722	**27.99**	
28mm	1	PB3728	**33.56**	

Quarter Turn Ball Valve (Nickel Plated Brass)	Pack Qty.	Code No.	Price Each £	
15mm	5	PB6715	**22.21**	
22mm	2	PB6722	**29.04**	
28mm	2	PB6728	**35.99**	

Ball Valve (Brass) (use to convert Unvalved to Valved version)	Pack Qty.	Code No.	Price Each £	
15mm x 15mm (Socket/Spigot)	5	PB4015	**19.31**	

Thermostatic Radiator Valve (Plated Brass) (All include MDPE 12 Bar Plastic Pipe Stiffener)	Pack Qty.	Code No.	Price Each £	
10mm	1	PB3310	**39.10**	
15mm	1	PB3315	**39.10**	

Radiator/Lockshield Valve (Plated Brass) (All include MDPE 12 Bar Plastic Pipe Stiffener)	Pack Qty.	Code No.	Price Each £	
10mm	1	PB3210	**9.73**	
15mm	1	PB3215	**9.73**	

Radiator Connector (Bend "RCB") (Pipe stiffeners must be used on each end)	Pack Qty.	Code No.	Price Each £	
10mm	10	PB3910	1.86	
15mm	10	PB3915	2.04	

Bend Former (Bend radius is 8 x Pipe diameter)	Pack Qty.	Code No.	Price Per Pack £	
15mm	5	PB6315	9.11	
22mm	5	PB6322	12.72	

Radiator Terminal Plate	Pack Qty.	Code No.	Price Each £	
Radiator Terminal Plate	10	RTP10	8.45	

Male BSP Adaptor (DZR Brass Body) (Taper BSP threads to BS21 only use PTFE tape to seal threads)	Pack Qty.	Code No.	Price Each £	
10mm x 1/4"	10	PB4310	8.53	
10mm x 3/8"	10	PB431038	8.53	
15mm x 1/2"	10	PB4315	9.03	
22mm x 3/4"	10	PB4322	13.21	
28mm x 1"	5	PB4328	17.51	

Female BSP Adaptor (DZR Brass Body) (Parallel BSP threads to BS21 only use PTFE tape to seal threads)	Pack Qty.	Code No.	Price Each £	
10mm x 1/4"	10	PB4410	9.61	
10mm x 3/8"	10	PB441038	9.61	
15mm x 1/2"	10	PB4415	8.95	
15mm x 3/4"	10	PB441534	10.22	
22mm x 3/4"	10	PB4422	13.36	
28mm x 1"	5	PB4428	14.64	

MDPE Polyfast Adaptor (Cold Water Only) (All include MDPE 12 Bar Plastic Pipe Stiffener)	Pack Qty.	Code No.	Price Each £	
15mm x 20mm	5	PB422015	4.11	
15mm x 25mm	5	PB422515	5.07	
22mm x 25mm	5	PB422522	5.26	
22mm x 32mm	5	PB423222	10.04	
28mm x 32mm	5	PB423228	10.52	

Spigot Draincock (Brass)	Pack Qty.	Code No.	Price Each £	
15mm	10	PB3615	8.54	

PolyPlumb

Pipe Stiffener (Plastic) (Must be used with Polybutylene Pipe)	Pack Qty.	Code No.	Price Per Pack £	
10mm	20	PB6410	6.94	
15mm	50	PB6415	16.89	
22mm	50	PB6422	21.03	
28mm	20	PB6428	12.51	

Pipe Stiffener (Stainless Steel)	Pack Qty.	Code No.	Price Per Pack £	
10mm	20	PB6410M	8.21	
15mm	50	PB6415M	20.01	
22mm	50	PB6422M	24.93	

PolyPlumb Bulldog Clips Polypropylene	Pack Qty.	Code No.	Price Per Pack £	
15mm	50	PB2115	5.86	
22mm	50	PB2122	8.81	
28mm	50	PB2128	12.10	

Nail-In Clips - Polypropylene	Pack Qty.	Code No.	Price Per Pack £	
10mm	50	PB2210	7.30	
15mm	50	PB2215	12.14	
22mm	50	PB2222	12.14	
28mm	50	PB2228	14.78	

Snap-Fit Clips - Polypropylene	Pack Qty.	Code No.	Price Per Pack £	
10mm	50	PB2310	8.24	
15mm	50	PB2315	12.54	
22mm	50	PB2322	12.54	
28mm	50	PB2328	17.01	

Pipe Clip Spacer - Polypropylene	Pack Qty.	Code No.	Price Per Pack £	
10mm	20	PB2410	4.52	
15mm	20	PB2415	4.17	
22mm	20	PB2422	5.58	
28mm	20	PB2428	7.39	

Spares Component Kit	Pack Qty.	Code No.	Price Each £	
10mm	10	PB9510	2.10	
15mm	10	PB9515	1.35	
22mm	10	PB9522	1.81	
28mm	5	PB9528	4.97	

Conical E.P.D.M. Sealing Washer (For Tap Connector with Brass Nut)	Pack Qty.	Code No.	Price Per Pack £	
1/2″	20	PB9312	3.90	
3/4″	20	PB9334	3.90	

Flat E.P.D.M. Sealing Washer (For Hand Tightened Tap Connector)	Pack Qty.	Code No.	Price Per Pack £	
1/2″	20	PB9412	3.90	
3/4″	20	PB9434	3.90	

'O' Rings E.P.D.M. Rubber (Must be lubricated)	Pack Qty.	Code No.	Price Per Pack £	
3/4″	20	PB9034	7.53	

Valve Tidy Cover - Polypropylene	Pack Qty.	Code No.	Price Each £	
For 10mm/8mm pipe	6	VT149	5.72	

Junction Inspection Box - Polypropylene	Pack Qty.	Code No.	Price Each £	
Junction Box (75mm deep - grey)	1	JIB1	5.40	
Junction Box Lid (12mm plywood)	1	JIB2	1.75	
Junction Box (65mm deep - black)	1	JIB3	5.27	

Silicone Lubricant, Solvent Cement and Cleaning Fluid	Pack Qty.	Code No.	Price Each £	
Silicone Lubricant 100gm Screw Top Jar	10	SG100	12.25	
Solvent Cement c/w Brush 125ml (BS6209)	10	SC125	9.45	
Solvent Cement c/w Brush 250ml (BS6209)	10	SC250	14.40	
Solvent Cement c/w Brush 500ml (BS6209)	10	SC500	26.10	
Cleaning Fluid 250ml Tin	10	CF250	10.30	

Boiler Overflow Pipe Guard	Pack Qty.	Code No.	Price Each £	
Boiler Overflow Pipe Guard (c/w x 2 Pipe Clips)	1	BOPG50	5.94	

Self Adhesive Aluminium Tape	Pack Qty.	Code No.	Price Each £	
48mm wide x 46 metres long (Do not stick to PolyPlumb pipes)	24	ALTP	13.68	

PolyPlumb

System Test Kit	Pack Qty.	Code No.	Price Each £
System Test Kit	1	PB993	**487.00**

Underfloor Pipe Duct (PVCu)	Pack Qty.	Code No.	Price Each £
50mm depth x 150mm width x 3 metre for 10, 15 & 22mm pipe (requires 12mm thickness cover board)	5	FD50	**16.99**
70mm depth x 150mm width x 3 metre for 28mm pipe, duct only - fittings fabricated on site (requires 12mm cover board)	5	FD70	**21.16**

Push-Fit Union (PVCu)	Pack Qty.	Code No.	Price Each £
Double Socket for 50mm only	10	FD52	**2.04**

Push-Fit 90° Angle (PVCu)	Pack Qty.	Code No.	Price Each £
Double Socket for 50mm only	10	FD53	**3.72**

Push-Fit 90° Tee (PVCu)	Pack Qty.	Code No.	Price Each £
Triple Socket for 50mm only	10	FD54	**4.15**

Push-Fit End Cap (PVCu)	Pack Qty.	Code No.	Price Each £
Single Socket for 50mm only (insert Solvent Weld Pipe Clips and Base)	10	FD55	**1.24**

Solvent Weld Pipe Clips (For use with PVCu Pipe Duct)	Pack Qty.	Code No.	Price Per Pack £
15mm (ABS)	100	FDB15	**5.22**
22mm (ABS)	100	FDB22	**7.48**
28mm (ABS)	100	FDB28	**9.76**
Pipe Clip Base Plate (PVC)	100	FDB93	**0.37**

Pipe Cutters Standard	Pack Qty.	Code No.	Price Each £
V Bladed Standard Cutter 10mm to 22mm	1	PB781	**17.80**

Pipe Cutters Ratchet	Pack Qty.	Code No.	Price Each £
Ratchet Type Cutters	1	PB778	**27.00**
Replacement Blade for Ratchet Cutter	1	PB779	**14.31**

PolyMax

PolyMax

NEW

Streamline push fit plumbing

PolyMax is our newest plumbing fitting range, introduced after extensive research, to meet consumer and installer demand.

Available in 15mm and 22mm sizes, PolyMax fittings are slim, sleek and attractive, making PolyMax the perfect choice for surface mounted installations. PolyMax is easily demounted using our handy release tool. Use PolyMax with Polypipe white polybutylene flexible pipe, using a Polypipe metal or plastic pipe stiffener. For extra security, choose the new Polypipe sealed stiffener.

PolyMax can be used on a wide range of home improvement and refit projects, including hot and cold water systems.

NEW

Straight Coupler	Pack Qty.	Code No.	Price Each £	
15mm	10	MAX015	1.68	
22mm	10	MAX022	2.37	

Socket Reducer	Pack Qty.	Code No.	Price Each £	
15mm x 10mm	10	MAX1815	2.75	
22mm x 15mm (not suitable for use with compression fittings)	10	MAX1822	2.12	

Elbow	Pack Qty.	Code No.	Price Each £	
15mm	10	MAX115	2.05	
22mm	10	MAX122	3.01	

Spigot Elbow	Pack Qty.	Code No.	Price Each £	
10mm	10	MAX1010	3.01	
15mm	10	MAX1015	2.05	

Equal Tee	Pack Qty.	Code No.	Price Each £	
15mm	10	MAX215	2.89	
22mm	10	MAX222	3.93	

End Reduced Tee	Pack Qty.	Code No.	Price Each £	
22mm x 15mm x 22mm	5	MAX1422	3.93	

Branch Reduced Tee	Pack Qty.	Code No.	Price Each £	
22mm x 22mm x 10mm	5	MAX112210	3.93	
22mm x 22mm x 15mm	5	MAX1122	3.93	

Branch and One End Reduced Tee	Pack Qty.	Code No.	Price Each £	
22mm x 15mm x 15mm	5	MAX1522	3.93	

Straight Tap Connector (Brass Connecting Nut)	Pack Qty.	Code No.	Price Each £	
15mm x 3/4" (1)	5	MAX71534	3.26	

(1) Complete with fibre sealing washer
(tighten by hand plus a further 1/6 of a turn with a spanner)

Hand Tighten Tap Connector (Not suitable for central heating)	Pack Qty.	Code No.	Price Each £	
15mm x 1/2"	10	MAX2715	2.34	
22mm x 3/4"	5	MAX2722	3.03	

Plumbing & Heating Fittings

PolyMax

Spigot Blank Ends (Not suitable for use with compression fittings)	Pack Qty.	Code No.	Price Each £	
10mm	10	FIT910	**0.92**	
15mm	10	FIT915	**0.85**	
22mm (with reinforcing sleeve)	10	FIT922	**1.04**	

Radiator Connector (Bend "RCB") (Pipe stiffeners must be used on each end)	Pack Qty.	Code No.	Price Each £	
10mm	10	PB3910	**1.86**	
15mm	10	PB3915	**2.04**	

Bend Former (Bend radius is 8 x pipe diameter)	Pack Qty.	Code No.	Price Each £	
15mm	5	PB6315	**9.11**	
22mm	5	PB6322	**12.72**	

Pipe Stiffener - Plastic (Must be used with polybutylene pipe)	Pack Qty.	Code No.	Price Each £	
10mm	20	PB6410	**6.94**	
15mm	50	PB6415	**16.89**	
22mm	50	PB6422	**21.03**	
28mm	20	PB6428	**12.51**	

Pipe Stiffener (Stainless Steel)	Pack Qty.	Code No.	Price Each £	
10mm	20	PB6410M	**8.21**	
15mm	50	PB6415M	**20.01**	
22mm	50	PB6422M	**24.93**	

Sealed Stiffener - Plastic (Not for use with PolyPlumb)	Pack Qty.	Code No.	Price Each £	
15mm	50	PB6415S	**TBC**	COMING SOON
22mm	50	PB6422S	**TBC**	

Fitting Release Aid	Pack Qty.	Code No.	Price Each £	
Set of 4 for 10mm, 15mm, 22mm and 28mm fittings, a useful tool to assist in demounting PolyMax and PolyFit fittings, but not essential	Per Set	FITAID	**2.04**	

Nail-In Clips - Polypropylene	Pack Qty.	Code No.	Price Each £	
10mm	50	FIT2210	**10.98**	
15mm	50	FIT2215	**14.89**	
22mm	50	FIT2222	**18.81**	
28mm	50	FIT2228	**21.94**	

Poly**Fit**

Quickfix push fit plumbing

PolyFit is our hand demountable white, push fit plumbing system, offering maximum flexibility and adjustability.

PolyFit features a one step jointing operation for quick and easy installation. PolyFit leads the market in speed to fit. If you need to adjust a fitting joint during the installation process, PolyFit fittings can be quickly demounted by hand, or by using our release tool.

Use PolyFit with Polypipe white polybutylene flexible pipe, using a Polypipe metal or plastic pipe stiffener. For extra security, choose the new Polypipe sealed stiffener.

PolyFit can be used on a wide range of contract and retrofit projects, including hot and cold water systems, and is particularly suitable for first fix installations.

Straight Coupler	Pack Qty.	Code No.	Price Each £
10mm	10	FIT010	2.28
15mm	10	FIT015	1.68
22mm	10	FIT022	2.65
28mm	5	FIT028	6.86

Socket Reducer	Pack Qty.	Code No.	Price Each £
15mm x 10mm	10	FIT1815	1.95
22mm x 15mm (not suitable for use with compression fittings)	10	FIT1822	2.53
28mm x 15mm (not suitable for use with compression fittings)	10	FIT182815	5.33
28mm x 22mm (not suitable for use with compression fittings)	5	FIT1828	5.70

Reducing Coupler	Pack Qty.	Code No.	Price Each £
15mm x 10mm	5	FIT5815	4.06
22mm x 10mm	5	FIT582210	5.01
22mm x 15mm	5	FIT5822	4.78

Elbow	Pack Qty.	Code No.	Price Each £
10mm	10	FIT110	2.81
15mm	10	FIT115	2.00
22mm	10	FIT122	3.17
28mm	5	FIT128	7.83

Spigot Elbow	Pack Qty.	Code No.	Price Each £
10mm	10	FIT1010	3.47
10mm x 15mm	10	FIT101510	3.70
15mm	10	FIT1015	3.91
22mm (not suitable for use with compression fittings)	10	FIT1022	5.95

Equal Tee	Pack Qty.	Code No.	Price Each £
10mm	10	FIT210	3.29
15mm	10	FIT215	2.90
22mm	10	FIT222	4.29
28mm	5	FIT228	11.03

PolyFit

End Reduced Tee	Pack Qty.	Code No.	Price Each £
15mm x 10mm x 15mm	5	FIT1415	**4.59**
22mm x 15mm x 22mm	5	FIT1422	**4.84**
28mm x 22mm x 28mm	5	FIT1428	**12.47**

Branch Reduced Tee	Pack Qty.	Code No.	Price Each £
15mm x 15mm x 10mm	5	FIT1115	**4.40**
22mm x 22mm x 10mm	5	FIT112210	**4.84**
22mm x 22mm x 15mm	5	FIT1122	**4.84**
28mm x 28mm x 22mm	5	FIT1128	**12.47**

Branch and One End Reduced Tee	Pack Qty.	Code No.	Price Each £
15mm x 10mm x 10mm	5	FIT1515	**4.84**
22mm x 15mm x 15mm	5	FIT1522	**4.84**
28mm x 22mm x 22mm	5	FIT1528	**12.47**

Two Ends Reduced Tee	Pack Qty.	Code No.	Price Each £
15mm x 15mm x 22mm	5	FIT1622	**4.92**

Spigot Blank Ends (Not suitable for use with compression fittings)	Pack Qty.	Code No.	Price Each £
10mm	10	FIT910	**0.92**
15mm	10	FIT915	**0.85**
22mm (with reinforcing sleeve)	10	FIT922	**1.04**

Socket Blank Ends	Pack Qty.	Code No.	Price Each £
10mm	10	FIT1910	**2.27**
15mm	10	FIT1915	**2.28**
22mm	10	FIT1922	**2.76**
28mm	5	FIT1928	**3.89**

Straight Tap Connector (Brass Connecting Nut)	Pack Qty.	Code No.	Price Each £
15mm x 1/2" (1)	10	FIT715	**3.39**
15mm x 3/4" (2)	5	FIT71534	**3.99**
22mm x 3/4" (2)	5	FIT722	**4.41**

(1) Complete with E.P.D.M. Sealing Washer. Spare flat seal included
    (tighten by hand plus a further 1/4 of a turn with a spanner)
(2) Complete with fibre sealing washer
    (tighten by hand plus a further 1/6 of a turn with a spanner)

Plumbing & Heating Fittings

Hand Tighten Tap Connector (Not suitable for central heating)	Pack Qty.	Code No.	Price Each £
10mm x 1/2″	10	FIT271012	3.25
15mm x 1/2″	10	FIT2715	1.89
15mm x 3/4″	5	FIT271534	4.14
22mm x 3/4″	5	FIT2722	2.84

Bent Tap Connector (Brass Connecting Nut)	Pack Qty.	Code No.	Price Each £
15mm x 1/2″	10	FIT1715	4.26

Complete with E.P.D.M. Sealing Washer. Spare flat seal included
(tighten by hand plus a further 1/4 of a turn with a spanner)

Tank Connector (Cold water only)	Pack Qty.	Code No.	Price Each £
15mm x 1/2″	10	FIT3815	2.90
22mm x 3/4″	10	FIT3822	3.70

Complete with E.P.D.M. Sealing Washer (tighten by hand)

Wall Plate Elbow (Brass) (Use PTFE tape to seal threads)	Pack Qty.	Code No.	Price Each £
15mm x 1/2″ BSP	5	FIT1315	16.71

Polybutylene Double Sided Manifold	Pack Qty.	Code No.	Price Each £
22mm x 10mm – 2 Port (Socket/Socket)	5	FIT2822	8.72
22mm x 10mm – 4 Port (Socket/Socket)	5	FIT4822	10.04

Polybutylene Single Sided Manifold	Pack Qty.	Code No.	Price Each £
22mm x 10mm – 4 Port (Socket/Socket)	1	FIT7322104	10.29
22mm x 15mm – 3 Port (Socket/Socket)	1	FIT7322153	8.62

Stopcock (Cold water only)	Pack Qty.	Code No.	Price Each £
15mm x 15mm	5	FIT2615	9.34
22mm x 22mm	5	FIT2622	12.60

MDPE Stopcock (Cold water only)	Pack Qty.	Code No.	Price Each £
20mm MDPE x 15mm	5	FIT262015	11.85
25mm MDPE x 22mm	5	FIT262522	17.15

PolyFit

Gate Valve	Pack Qty.	Code No.	Price Each £
15mm	5	FIT3115	19.11
22mm	5	FIT3122	23.61

Shut-Off Valve (White) (Not suitable for central heating)	Pack Qty.	Code No.	Price Each £
15mm x 15mm Warm/Cold (Please note these valves now contain a plain white index)	5	FIT5915	6.29

Appliance Valve (White) (Not suitable for central heating)	Pack Qty.	Code No.	Price Each £
15mm x 3/4" Warm/Cold (Please note these valves now contain a plain white index)	5	FIT6115	5.56

Service Valve (White) (Not suitable for central heating)	Pack Qty.	Code No.	Price Each £
15mm x 1/2" (Please note these valves now contain a plain white index)	5	FIT6515	7.93

Chrome Plated Service Valve (Brass)	Pack Qty.	Code No.	Price Each £
15mm x 15mm	5	FIT8515	19.96
22mm x 22mm	5	FIT8522	44.74

Chrome Plated Service Valve with Tap Connector (Brass)	Pack Qty.	Code No.	Price Each £
15mm x 1/2"	5	FIT8615	19.77
22mm x 3/4"	5	FIT8622	48.53

Male BSPT Adaptor (DZR Brass Body) (Taper BSP threads to BS21 only use PTFE tape to seal threads)	Pack Qty.	Code No.	Price Each £
10mm x 1/2"	10	FIT431012	9.09
15mm x 1/2"	10	FIT4315	9.26
22mm x 3/4"	10	FIT4322	15.06
28mm x 1"	5	FIT4328	29.60

Female BSP Adaptor (DZR Brass Body) (Taper BSP threads to BS21 only use PTFE tape to seal threads)	Pack Qty.	Code No.	Price Each £
10mm x 1/2"	10	FIT441012	7.07
15mm x 1/2"	10	FIT4415	10.25
22mm x 3/4"	10	FIT4422	14.69

MDPE x PolyFit Adaptor (Cold water only)	Pack Qty.	Code No.	Price Each £
20mm x 15mm	5	FIT422015	8.06
25mm x 15mm	5	FIT422515	12.03
25mm x 22mm	5	FIT422522	9.52

Spigot Draincock (Brass)	Pack Qty.	Code No.	Price Each £
15mm	10	FIT3615	11.14

Radiator Connector (Bend "RCB") (Pipe stiffeners must be used on each end)	Pack Qty.	Code No.	Price Each £
10mm	10	PB3910	1.86
15mm	10	PB3915	2.04

Bend Former (Bend radius is 8 x pipe diameter)	Pack Qty.	Code No.	Price Per Pack £
15mm	5	PB6315	9.11
22mm	5	PB6322	12.72

Spares Component Kit	Pack Qty.	Code No.	Price Each £
10mm	10	FIT9510	2.14
15mm	10	FIT9515	1.38
22mm	10	FIT9522	1.76
28mm	5	FIT9528	5.06

Fitting Release Aid	Pack Qty.	Code No.	Price Per Pack £
Set of 4 for 10mm, 15mm, 22mm and 28mm fittings, a useful tool to assist in demounting PolyMax and PolyFit fittings, but not essential	Per Set	FITAID	2.04

Conical E.P.D.M. Sealing Washer (For Tap Connector with Brass Nut)	Pack Qty.	Code No.	Price Per Pack £
1/2"	20	PB9312	3.90
3/4"	20	PB9334	3.90

Flat E.P.D.M. Sealing Washer (For Hand Tightened Tap Connector)	Pack Qty.	Code No.	Price Per Pack £
1/2"	20	PB9412	3.90
3/4"	20	PB9434	3.90

'O' Rings E.P.D.M. Rubber (Must be lubricated)	Pack Qty.	Code No.	Price Per Pack £
3/4"	20	PB9034	7.53

PolyFit

Nail-In Clips - Polypropylene	Pack Qty.	Code No.	Price Per Pack £
10mm	50	FIT2210	10.98
15mm	50	FIT2215	14.89
22mm	50	FIT2222	18.81
28mm	50	FIT2228	21.94

Pipe Stiffener (Plastic) (Must be used with Polybutylene Pipe)	Pack Qty.	Code No.	Price Per Pack £
10mm	20	PB6410	6.94
15mm	50	PB6415	16.89
22mm	50	PB6422	21.03
28mm	20	PB6428	12.51

Pipe Stiffener (Stainless Steel)	Pack Qty.	Code No.	Price Per Pack £
10mm	20	PB6410M	8.21
15mm	50	PB6415M	20.01
22mm	50	PB6422M	24.93

Sealed Stiffener - Plastic (Not for use with PolyPlumb)	Pack Qty.	Code No.	Price Per Pack £
15mm	50	PB6415S	TBC
22mm	50	PB6422S	TBC

COMING SOON

Pipe Cutters Standard	Pack Qty.	Code No.	Price Each £
V Bladed Standard Cutter 10mm to 22mm	1	PB781	17.80

Pipe Cutters Ratchet	Pack Qty.	Code No.	Price Each £
Ratchet Type Cutters	1	PB778	27.00
Replacement Blade for Ratchet Cutter	1	PB779	14.31

Self Adhesive Aluminium Tape	Pack Qty.	Code No.	Price Each £
48mm wide x 46 metres long (Do not stick to PolyPlumb pipes)	24	ALTP	13.68

System Test Kit	Pack Qty.	Code No.	Price Each £
System Test Kit	1	PB993	487.00

Radiator Terminal Plate	Pack Qty.	Code No.	Price Each £
Radiator Terminal Plate	10	RTP10	8.45

PolyFit Hoses

PolyFit

Hoses

Our flexible hose connector range provides the choice of length, end connection and valve options, suitable for a wide range of projects.

Many of our flexible connectors include the PolyFit one step joint feature, which are quick and easy to install and are ideal for use in tricky to reach or tight locations.

All PolyFit hoses which have a tap connector nut contain captive rubber seals, ensuring that seals are not lost of damaged on site.

Plumbing & Heating Fittings

Flexible Hose Tap Connector (Not suitable for central heating)	Pack Qty.	Code No.	Price Each £	
150mm x 15mm x 1/2"	2	FIT5715	8.18	
300mm x 15mm x 1/2"	2	FIT6815	7.50	
300mm x 15mm x 3/4"	2	FIT681534	9.44	
300mm x 22mm x 3/4"	2	FIT6822	8.62	
500mm x 15mm x 1/2"	2	FIT8315	10.79	
500mm x 15mm x 3/4"	2	FIT831534	12.20	
500mm x 22mm x 3/4"	2	FIT8322	13.00	
1000mm x 15mm x 1/2"	2	FIT8015	20.76	
1000mm x 15mm x 3/4"	2	FIT801534	23.44	
1000mm x 22mm x 3/4"	2	FIT8022	26.28	

Flexible Hose Tap Connector with Service Valve (Not suitable for central heating)	Pack Qty.	Code No.	Price Each £	
300mm x 15mm x 1/2"	2	FIT8415	19.84	
300mm x 22mm x 3/4"	2	FIT8422	36.16	
500mm x 15mm x 1/2"	2	FIT8715	25.76	
500mm x 15mm x 3/4"	2	FIT871534	28.34	

Flexible PolyFit Connector with Service Valve (Not suitable for central heating)	Pack Qty.	Code No.	Price Each £	
300mm x 15mm x 15mm	2	FIT8815	20.58	
500mm x 15mm x 15mm	2	FIT8915	23.63	

Flexible PolyFit Connector (Not suitable for central heating)	Pack Qty.	Code No.	Price Each £	
300mm x 15mm x 15mm	2	FIT8115	10.16	
300mm x 22mm x 22mm	2	FIT8122	12.44	
500mm x 15mm x 15mm	2	FIT8215	14.93	
500mm x 22mm x 22mm	2	FIT8222	16.98	

Monobloc Mixer Tap Flexible Connector (Not suitable for central heating)	Pack Qty.	Code No.	Price Per Pair £	
300mm x 15mm x M10	2	FIT7515M10	15.08	
300mm x 15mm x M12	2	FIT7515M12	15.08	

Supplied in pairs with offset nuts to aid installation to mixer tap

PolyFit Hoses

Compression Flexible Hose Tap Connector (Not suitable for central heating)	Pack Qty.	Code No.	Price Each £	
300mm x 15mm x 1/2"	2	FIT9615	7.98	
300mm x 22mm x 3/4"	2	FIT9622	8.83	
500mm x 15mm x 1/2"	2	FIT9815	11.33	
500mm x 22mm x 3/4"	2	FIT9822	13.58	

Compression Flexible Hose Tap Connector with Service Valve (Not suitable for central heating)	Pack Qty.	Code No.	Price Each £	
300mm x 15mm x 1/2"	2	FIT9715	18.58	
300mm x 22mm x 3/4"	2	FIT9722	33.85	

90° Elbow Flexible Hose Connector	Pack Qty.	Code No.	Price Each £	
90° Elbow	2	FIT7115	10.66	

PolySure

Permanent press fit plumbing

PolySure is our radial press fit system, available in UK sizes, and installed using specialist crimping tools.

PolySure features secure, tamperproof jointing technology for a permanent fit. The slim profile fittings are ideal for use in visible installations. An inbuilt location washer ensures the crimping tool jaws are correctly positioned for accurate fitting and a visual socket depth indicator and double O-ring seal provides enhanced jointing.

Use PolySure with Polypipe white or grey polybutylene flexible pipe.

PolySure can be used in any hot and cold water installation but is particularly suited to buildings with high levels of public access traffic, where security and joint integrity are paramount.

PolySure

Straight Couplers	Pack Qty.	Code No.	Price Each £
10mm	10	SUR010	5.91
15mm	10	SUR015	5.09
22mm	10	SUR022	10.16
28mm	10	SUR028	15.30

Socket x Socket Reducer	Pack Qty.	Code No.	Price Each £
15mm x 10mm	10	SUR5815	6.08
22mm x 15mm	10	SUR5822	8.18
28mm x 15mm	10	SUR582815	13.82
28mm x 22mm	10	SUR5828	15.30

90° Elbow	Pack Qty.	Code No.	Price Each £
10mm	10	SUR110	5.34
15mm	10	SUR115	5.42
22mm	10	SUR122	11.85
28mm	10	SUR128	17.22

Equal Tees	Pack Qty.	Code No.	Price Each £
15mm	10	SUR215	7.62
22mm	10	SUR222	16.74
28mm	10	SUR228	31.99

End Reduced Tees	Pack Qty.	Code No.	Price Each £
22mm x 15mm x 22mm	10	SUR1422	14.46
28mm x 22mm x 28mm	10	SUR1428	22.65

Branch Reduced Tees	Pack Qty.	Code No.	Price Each £
15mm x 15mm x 10mm	10	SUR1115	8.76
22mm x 22mm x 15mm	10	SUR1122	14.46
28mm x 28mm x 15mm	10	SUR112815	19.18
28mm x 28mm x 22mm	10	SUR1128	22.65

Branch and End Reduced Tees	Pack Qty.	Code No.	Price Each £
22mm x 15mm x 15mm	10	SUR1522	12.81
28mm x 22mm x 22mm	10	SUR1528	21.26

Straight Tap Connector	Pack Qty.	Code No.	Price Each £
15mm x 1/2" (1)	10	SUR715	10.62
15mm x 3/4" (2)	10	SUR71534	11.49
22mm x 3/4" (2)	10	SUR722	13.03

Plumbing & Heating Fittings

PolySure

Bent Tap Connector	Pack Qty.	Code No.	Price Each £	
15mm x 1/2" (1)	10	SUR1715	**10.68**	

(1) Complete with E.P.D.M. Sealing Washer. Spare flat seal included
   (tighten by hand plus a further 1/4 of a turn with a spanner)
(2) Complete with fibre sealing washer
   (tighten by hand plus a further 1/6 of a turn with a spanner)

Male BSP Adaptor	Pack Qty.	Code No.	Price Each £	
15mm x 1/2"	10	SUR4315	**4.33**	
22mm x 3/4"	10	SUR4322	**8.23**	
28mm x 1"	10	SUR4328	**12.15**	

Female BSP Adaptor	Pack Qty.	Code No.	Price Each £	
15mm x 1/2"	10	SUR4415	**5.66**	
22mm x 3/4"	10	SUR4422	**8.44**	
28mm x 1"	10	SUR4428	**15.58**	

Compression Adaptor	Pack Qty.	Code No.	Price Each £	
15mm	10	SUR5515	**14.67**	
22mm	10	SUR5522	**20.83**	

Standard Pressing Jaws Polypipe TH Can be used with Manual Pressing Tool (not 28mm) or Standard Battery Operated Pressing Gun	Pack Qty.	Code No.	Price Each £	
10mm	1	JAW10TH	**179.23**	
15mm	1	JAW15TH	**179.23**	
22mm	1	JAW22TH	**179.23**	
28mm	1	JAW28TH	**190.97**	

Mini Pressing Jaws Polypipe TH Profile Can only be used with Mini Battery Operated Pressing Gun	Pack Qty.	Code No.	Price Each £	
10mm	1	MJAW10TH	**140.48**	
15mm	1	MJAW15TH	**140.48**	
22mm	1	MJAW22TH	**140.48**	
28mm	1	MJAW28TH	**140.48**	

Pipe Cutters Standard	Pack Qty.	Code No.	Price Each £	
V Bladed Standard Cutter 10mm to 22mm	1	PB781	**17.80**	

Plumbing & Heating Fittings

Pipe Cutters Ratchet	Pack Qty.	Code No.	Price Each £	
Ratchet Type Cutters	1	PB778	**27.00**	
Replacement Blade for Ratchet Cutter	1	PB779	**14.31**	

Manual Pressing Tool	Pack Qty.	Code No.	Price Each £	
Manual Pressing Tool (Jaws purchased separately)	1	MANPRES	**170.86**	

Pipe Chamfering Tool	Pack Qty.	Code No.	Price Each £	
Universal Pipe Chamfering Tool	1	UNIPCT	**63.81**	

Individual Pipe Chamfering Tools	Pack Qty.	Code No.	Price Each £	
10mm*	1	10PCT	**27.70**	
15mm*	1	15PCT	**27.70**	
22mm*	1	22PCT	**28.20**	
28mm*	1	28PCT	**28.20**	
Set of 4 Pipe Chamfering Tools, 10, 15, 22 and 28mm**	1	SETPCT	**122.37**	

* Does not include handle
** Includes handle

Standard Battery Operated Pressing Gun	Pack Qty.	Code No.	Price Each £	
Standard Battery Operated Pressing Gun (Jaws purchased separately)	1	BATPRES	**POA**	

Mini Battery Operated Pressing Gun	Pack Qty.	Code No.	Price Each £	
Mini Battery Operated Pressing Gun, with battery level indicator (Jaws purchased separately)	1	MBATPRES	**POA**	

'O' Rings	Pack Qty.	Code No.	Price Per Pack £	
10mm	20	SUR9010	**4.71**	
15mm	20	SUR9015	**4.15**	
22mm	20	SUR9022	**8.03**	
28mm	20	SUR9028	**12.19**	

Press Sleeve and Washer	Pack Qty.	Code No.	Price Each £	
10mm	10	SUR9510	**1.48**	
15mm	10	SUR9515	**1.27**	
22mm	10	SUR9522	**2.55**	
28mm	10	SUR9528	**3.83**	

Underfloor Heating Systems

Polypipe manufactures the most comprehensive range of underfloor heating systems available for the UK market.

Our range combines versions of traditional underfloor systems and a number of innovative product solutions, designed to extend the suitability of underfloor heating to almost any installation scenario, from whole house to single room projects and for new build and renovation.

Use the quick reference guide below to find the right solution or, for more information, consult our Technical Specification Guide or use the online product selectors at **www.polypipe.com/plumbing-heating**

Traditional underfloor heating systems

Unique underfloor heating systems

You can find out more about Polypipe Underfloor Heating Systems at **www.polypipe.com/plumbing-heating**

Polypipe Grey Plumbing, Heating and Underfloor Heating Pipe - BS 7291 Class S

Barrier Polybutylene Pipe Coil (Grey)	Pack Qty.	Code No.	Price Each £
15mm x 50 metre Barrier	1	PB5015B	99.68
15mm x 80 metre Barrier	1	PB8015B	155.76
15mm x 100 metre Barrier	1	PB10015B	198.19
15mm x 120 metre Barrier	1	PB12015B	230.64
15mm x 150 metre Barrier	1	PB15015B	297.00

Polypipe Ultra Flexible Underfloor Heating Pipe (For Underfloor Heating Use Only) - EN15876

Underfloor Heating Pipe Polybutylene	Pack Qty.	Code No.	Price Each £
12mm x 25m Coil UFH Pipe	1	UFH2512B	35.50
12mm x 50m Coil UFH Pipe	1	UFH5012B	71.00
12mm x 80m Coil UFH Pipe	1	UFH8012B	113.60
15mm x 50m Coil UFH Pipe	1	UFH5015B	81.00
15mm x 80m Coil UFH Pipe	1	UFH8015B	129.60
15mm x 100m Coil UFH Pipe	1	UFH10015B	162.00
15mm x 120m Coil UFH Pipe	1	UFH12015B	194.40
15mm x 150m Coil UFH Pipe	1	UFH15015B	243.00
18mm x 120m Coil UFH Pipe	1	UFH12018B	252.00
18mm x 200m Coil UFH Pipe	1	UFH20018B	420.00
18mm x 300m Coil UFH Pipe	1	UFH30018B	630.00

NEW

Conduit Pipe

Conduit Polypropylene Pipe Coil	Pack Qty.	Code No.	Price Each £
15mm x 25 metre (Black)	1	CPC1525	27.30
15mm x 50 metre (Black)	1	CPC1550	54.91

Polypipe MCP Underfloor Heating Pipe
(For Underfloor Heating Use Only) - EN21003

Metal Composite Pipe	Pack Qty.	Code No.	Price Each £	
16mm x 80m Coil MCP UFH Pipe	1	MCP8016B	156.80	
16mm x 100m Coil MCP UFH Pipe	1	MCP10016B	196.00	
16mm x 120m Coil MCP UFH Pipe	1	MCP12016B	235.20	
16mm x 150m Coil MCP UFH Pipe	1	MCP15016B	294.00	NEW

Solid Floor System

Underfloor heating
for solid screeded floors

The Polypipe Solid Floor System features our famous red, lightweight floor panels that are laid to hold the pipe in place. Once the system is installed you simply lay the screed over the top.

Use with screeded floors in both new build and renovation projects.

We also provide clip rail and staple systems for Solid Floor Applications. Solid Floor Systems are compatible with our 15mm, 16mm and 18mm pipe ranges.

Floor Panel	Pack Qty.	Code No.	Price Each £	
Allow for overlap and waste when ordering				
1.2m x 1m	1	PB08576	10.64	

Clip Rails	Pack Qty.	Code No.	Price Each £	
200mm pipe centres (15mm pipe) & 200mm & 300mm pipe centres (18mm pipe). Use approx 1m/m² floor area and secure with standard Pipe Clip PB02911.				
15mm 8 x 2m pack (16m)	1	PB08515	53.78 per pack	
18mm 8 x 2m pack (16m)	1	PB08518	53.78 per pack	

Standard UFCH Pipe Clip	Pack Qty.	Code No.	Price Each £	
Standard UFCH Pipe Clip	250	PB02911	32.95 per pack	

UFCH Staple System	Pack Qty.	Code No.	Price Each £	
UFCH Staple Clip (60mm)	300	PB02930	52.00 per pack	
UFCH Staple Gun	1	PB02931	350.00	NEW

Edge Insulation	Pack Qty.	Code No.	Price Each £	
25m Coil	1	PB05855	32.95	

Long Radius Bend Former	Pack Qty.	Code No.	Price Each £	
For use as pipe guide at bottom of manifold - accepts 15mm conduit pipe	1	PB6325	16.34	

Underfloor Heating Systems

1 Insulation
2 Pipe
3 Solid floor plate
4 Screed

Floating Floor System

Underfloor heating
for floating floors

The Polypipe Floating Floor System features high density polystyrene floor panels that enhance insulation as well as providing the base for the heating pipes.

The system is designed for use with "dry build" floors laid directly over solid or timber sub bases in both new build and existing properties.

Floating Floor Systems are compatible with our 15mm and 18mm pipe systems.

Floor Panel Coverage approximately 14.4m² per 10 pack Floating Floor Panel - 100kN/m²	Pack Qty.	Code No.	Price Each £	
1.2m x 1.2m x 50mm	10	PB08587	183.08 per pack	

Single Heat Spreader Plate	Pack Qty.	Code No.	Price Each £	
15mm	5	PB207	29.70 per pack	
18mm	5	PB208	29.70 per pack	

1 Insulated floating floor panel
2 Heat spreader plate
3 Pipe
4 Structural floor

Underfloor Heating Systems

Suspended Floor System

Underfloor heating
for suspended floors

The Polypipe Suspended Floor System features double heat spreader plates, which diffuse heat across the entire floor surface. Now also available in fit from below format so you can still use this system, even if the floor above has already been installed.

For enhanced performance, especially over larger floor areas, use with our new Overlay™ Lite 15 panels for an integrated insulated solution.

The suspended floor systems are designed for use on timber suspended or battened floors.

For use with our 15mm pipe systems.

Double Heat Spreader Plate Pipe grooves at 125mm each side of centre line	Pack Qty.	Code No.	Price Each £	
For 15mm Pipe, 450mm x 1m span double indent	5	PB209	77.95	

FFB Double Heat Spreader Plate	Pack Qty.	Code No.	Price Each £	
For 15mm Pipe, 310mm x 1m span double indent	5	PB206	111.37	

Double Heat Spreader Plate

1 Ceiling
2 Supporting joists
3 Insulation
4 Double heat spreader plate
5 15mm Polybutylene barrier pipe
6 Structural floor

Fit From Below (FFB) Double Heat Spreader Plate

NEW

1 Ceiling
2 Supporting joists
3 Insulation
4 FFB Double heat spreader plate
5 15mm Polybutylene barrier pipe
6 Structural floor

Fit From Above With Overlay™ Lite 15*

NEW

1 Ceiling
2 Supporting joists
3 Board
4 Overlay™ Lite 15
5 15mm Polybutylene barrier pipe
6 Structural floor

*Refer to Overlay™ Lite 15 page for price

Underfloor Heating Systems

Modular Heating Panels (MHP) Floor System

Underfloor heating
for suspended floors

The unique and patented **Polypipe Modular Heating Panels (MHP)** is a system of pre-configured panels, which are connected together on site during installation.

MHP simplifies the installation of underfloor heating into upper floors. The factory configured panels come with heating pipe pre-installed and each panel is linked together prior to connection to the heat source. On site installation is quick and easy, with the panels fixed between the ceiling joists and accessible from above or below.

MHP is equally suitable for new build and retrofit projects.

MHP is compatible with our push fit and press fit fittings ranges.

MHP (Modular Heating Panel)	Pack Qty.	Code No.	Price Each £	
330mm x 1.3m	5	MHP33013	128.79 per pack	
380mm x 1.3m	5	MHP38013	128.79 per pack	
330mm x 2.0m	5	MHP33020	171.72 per pack	
380mm x 2.0m	5	MHP38020	171.72 per pack	
490mm x 1.3m	5	MHP49013	171.72 per pack	
490mm x 2.0m	5	MHP49020	228.96 per pack	

Underfloor Heating Systems

1 Ceiling
2 Supporting joists
3 30mm insulation
4 Heat diffusion foil
5 10mm pipe circuit
6 Structural floor

Overlay™ Floor System

Underfloor heating
that goes over the floor

The Polypipe Overlay™ System is a patented underfloor heating solution, which uses floor panels that are laid over the existing floor surface prior to finishing and covering. Pre-routed grooves in the floor panels and special end returns ensure that laying the pipe is quick and easy.

Overlay™ is offered in a range of panel types to suit different floor coverings and sizes. Overlay™ can be cost effectively installed into new build properties but is especially useful for retrofit projects where it is not practical to access the sub floor.

Overlay™ is compatible with our 12mm underfloor heating pipe range.

Choose **Overlay™** original floor panels for use with heavier floor coverings such as tiles and ceramics.

Overlay™

Overlay™ Floor Panel	Pack Qty.	Code No.	Price Each £	
800mm (L) x 600mm (W) x 18mm (D) Coverage approx. 4.8m² per 10 pack	10	PB08570	**191.07** per pack	
800mm (L) x 600mm (W) x 18mm (D) Coverage approx. 14·4m² per 30 pack	30	PB08571	**573.29** per pack	

End Returns (Overlay™ & Overlay™ Lite)	Pack Qty.	Code No.	Price Each £	
End Returns	10	PB08573	**29.99** per pack	

Polyurethane Expanding Foam Glue	Pack Qty.	Code No.	Price Each £	
Polyurethane Expanding Foam Glue (Overlay™)	1	PB776	**17.16**	

Adaptor Set (Overlay™ & Overlay™ Lite)	Pack Qty.	Code No.	Price Each £	
15mm x 12mm including Pipe Stiffeners per pack	2	PB181512	**5.15**	

Temperature Limiting Valve	Pack Qty.	Code No.	Price Each £	
Temperature Limiting Valve 5m² Overlay™ only	1	PB970010	**82.57**	

Underfloor Heating Systems

1 Fits over concrete or floorboards
2 600mm x 800mm x 18mm Overlay™ panel
3 12mm polybutylene barrier pipe
4 End return
5 Suitable for tiles and hard wood floors

Overlay™ Lite
Floor System

Underfloor heating
that goes over the floor

The Polypipe Overlay™ Lite System is a patented underfloor heating solution, which uses floor panels that are laid over the existing floor surface prior to finishing and covering.

Overlay™ Lite is a high compressive strength, lightweight insulated panel used for lightweight floor coverings, e.g. laminate, engineered wood and carpet.

Overlay™ Lite 15 is the latest addition to the range and allows 15mm pipe to be used with circuit coverage of 20m² per circuit. Therefore being suitable for larger areas or whole house installation.

Choose **Overlay™ Lite** floor panels for use with lighter floor coverings such as carpet and laminates.

Overlay™ Lite

Overlay™ Lite Floor Panel	Pack Qty.	Code No.	Price Each £	
1245mm (L) x 600mm (W) x 18mm (D) Coverage approx. 7.5m² per 10 pack	10	PB08010	297.39 per pack	
1245mm (L) x 600mm (W) x 18mm (D) Coverage approx. 15m² per 20 pack	20	PB08020	594.79 per pack	

Self Adhesive Aluminium Tape	Pack Qty.	Code No.	Price Each £	
48mm wide x 46 metres long	24	ALTP	13.68	

1 Fits over concrete or floorboards
2 Overlay™ Lite panel
3 Heat diffusion foil
4 12mm polybutylene barrier pipe
5 End return
6 10mm plywood lining
7 Suitable for laminate floors or carpet

Choose **Overlay™ Lite 15** floor panels, with 15mm pipe, for larger floor areas.

Overlay™ Lite 15

Overlay™ Lite 15 Floor Panel	Pack Qty.	Code No.	Price Each £	
1200mm (L) x 800mm (W) x 22mm (D) Coverage approx. 9.6m² per 10 pack	10	PB08030	380.64 per pack	
Connection / Return panel	10	PB08040	100.00 per pack	

Self Adhesive Aluminium Tape	Pack Qty.	Code No.	Price Each £	
48mm wide x 46 metres long	24	ALTP	13.68	

NEW

1 Fits over concrete or floorboards
2 Overlay™ Lite 15 panel
3 Heat diffusion foil
4 15mm polybutylene barrier pipe
5 End return
6 10mm plywood lining
7 Suitable for most floor coverings

Manifolds & Water Temperature Controls

Polypipe offers a broad range of manifold and water temperature controls for both traditional and underfloor heating applications.

Manifolds are used in all underfloor heating systems above 30m^2, irrespective of floor type. Manifolds are supplied complete and fixed with a wall mounting bracket. The manifold comes complete with a drain and air vent assembly, which can be positioned on either end of the manifold, and isolation valves are supplied separately for the supply end of the manifold.

We offer a range of 15mm push fit manifolds for use with 12mm and 15mm pipe systems and compression manifolds for use with our 16mm and 18mm pipe systems.

Each Polypipe manifold includes a flow meter on each flow port to provide a visual indicator of the flow through rate of each circuit.

Polypipe also offers a range of water temperature control units. These are used to reduce the water temperature for underfloor heating systems, when connected to the same boiler used for radiators or stored hot water, which operate at higher temperatures than underfloor systems.

Underfloor Heating Manifolds and Ancillaries

15mm Manifold Pushfit For use with 15mm and 12mm Overlay™ Systems	Pack Qty.	Code No.	Price Each £	
2 Port - Pushfit Manifold	1	PB12737	**177.90**	
3 Port - Pushfit Manifold	1	PB12738	**214.15**	
4 Port - Pushfit Manifold	1	PB12739	**263.56**	
5 Port - Pushfit Manifold	1	PB12740	**283.34**	
6 Port - Pushfit Manifold	1	PB12741	**337.71**	
7 Port - Pushfit Manifold	1	PB12742	**370.65**	
8 Port - Pushfit Manifold	1	PB12743	**411.83**	
9 Port - Pushfit Manifold	1	PB12744	**448.06**	
10 Port - Pushfit Manifold	1	PB12745	**485.96**	
11 Port - Pushfit Manifold	1	PB12746	**527.14**	
12 Port - Pushfit Manifold	1	PB12747	**568.33**	

15mm Manifold Extension Kit	Pack Qty.	Code No.	Price Each £	
Underfloor Central Heating Manifold Extension Kit	1	PB12736	**102.29**	

16mm and 18mm Compression Manifold For use with 16mm MCP and 18mm systems Use with Manifold Unions	Pack Qty.	Code No.	Price Each £	
2 Port - Compression Manifold	1	PB08351	**177.90**	
3 Port - Compression Manifold	1	PB08392	**214.15**	
4 Port - Compression Manifold	1	PB08459	**263.56**	
5 Port - Compression Manifold	1	PB08462	**283.34**	
6 Port - Compression Manifold	1	PB08479	**337.71**	
7 Port - Compression Manifold	1	PB08558	**370.65**	
8 Port - Compression Manifold	1	PB08563	**411.83**	
9 Port - Compression Manifold	1	PB08564	**448.06**	
10 Port - Compression Manifold	1	PB08572	**485.96**	
11 Port - Compression Manifold	1	PB08588	**527.14**	
12 Port - Compression Manifold	1	PB08589	**568.33**	

16mm and 18mm Manifold Unions To be used on each Manifold Port	Pack Qty.	Code No.	Price Each £	
16mm	1	PB07729	**4.50**	
18mm	1	PB07730	**4.50**	

UFCH Manifold Bends (90°)	Pack Qty.	Code No.	Price Each £	
Allows pump unit and manifold to be corner mounted, can be used with UFCH Control Pack or Modulating Pump Unit (Pair)	1	PB12735	45.65	

Isolation Valves	Pack Qty.	Code No.	Price Each £	
1 inch - Isolation Valves - use to connect manifolds to both UFCH Control Pack & Modulating Pump Unit (Pair)	1	PB01732	36.35	

Manifold Spares and Accessories

Manifold Flow Meter	Pack Qty.	Code No.	Price Each £	
Manifold Flow Meter	1	PB127FM	17.00	

Manifold Balancing Valve	Pack Qty.	Code No.	Price Each £	
Manifold Balancing Valve	1	PB127BV	12.98	

Manifold Blue Cap	Pack Qty.	Code No.	Price Each £	
Manifold Blue Cap	1	PB127BC	1.86	

Manifold End Set	Pack Qty.	Code No.	Price Each £	
Manifold End Set (Pair)	1	PB127ES	43.28	

Temperature Gauge	Pack Qty.	Code No.	Price Each £	
Temperature Gauge	1	PB127TG	16.38	

Manifolds & Water Temperature Controls

Water Temperature Controls and Accessories

Multiple Room Systems

Manifold Control Pack	Pack Qty.	Code No.	Price Each £	
UFCH Control Pack - Includes EUP Pump, UFCH Mixer Valve, bend and adaptors	1	PB970025	450.00	

2 Port Zone Valve	Pack Qty.	Code No.	Price Each £	
2 Port Spring Return Zone Valve	1	PB9700ZV	75.00	

UFCH Mixing Valve	Pack Qty.	Code No.	Price Each £	
22mm	1	PB219058	144.67	
28mm	1	PB219059	161.49	

Single Room Systems

Single Room Control Units Zonal Regulation Units (ZRU)	Pack Qty.	Code No.	Price Each £	
ZRU Single circuit	1	PB970018	509.80	

Single Room Control Units Zonal Regulation Units (ZRU)	Pack Qty.	Code No.	Price Each £	
ZRU 2/3 circuit	1	PB970028	529.80	NEW UNIT

Temperature Limiting Valve	Pack Qty.	Code No.	Price Each £	
Temperature Limiting Valve 5m^2 Overlay™ only	1	PB970010	82.57	

Room Temperature Controls

Polypipe supplies a comprehensive range of room temperature control products for use on both Polypipe Underfloor Heating Systems and for general use to control heating temperatures in different rooms or control zones.

The range is designed to enable users to configure their heating system to create their preferred balance of comfort and efficiency. Unique programming functions also provide the perfect control solution for Polypipe Underfloor Heating Systems.

Polypipe Room Temperature Controls are available in a wide range of options, including dial, digital and programmable room thermostats, in both wired and RF version, time clocks and master and slave systems.

Use our online controls selector tool for help with selecting the right controls system at **www.polypipe.com/plumbing-heating**

Room Temperature Controls

Room Temperature Controls

UFCH Valve Actuators	Pack Qty.	Code No.	Price Each £	
2 Wire	1	PB00401	**30.15**	
4 Wire	1	PB00402	**49.32**	

Room Thermostats	Pack Qty.	Code No.	Price Each £	
Dial Room Thermostat	1	PBRS	**45.00**	
Dial Room Thermostat RF	1	PBRS RF	**65.00**	
Digital Thermostat	1	PBDIG	**65.00**	
Digital Thermostat RF	1	PBDIG RF	**80.00**	
Programmable Room Thermostat	1	PBPRP	**83.83**	
Programmable Room Thermostat RF	1	PBPRPS RF	**115.00**	

Time Clocks	Pack Qty.	Code No.	Price Each £	
2 Channel	1	PB2CTC	**60.00**	
4 Channel RF	1	PB4CTC RF	**100.00**	

Wiring Centres For wired room thermostats and clocks	Pack Qty.	Code No.	Price Each £	
Single Zone Master Control Unit - Provides wiring connections for Boiler, Zone Valve, UFH Pump and Power Supply and Single Room Thermostat	1	PB1ZM	**91.80**	
4 Zone Slave Unit - Plug-in connection to Master Unit to provide 4 Control Zones	1	PB4ZS	**80.02**	
6 Zone Slave Unit - Plug-in connection to Master Unit to provide 6 Control Zones	1	PB6ZS	**97.20**	

Wiring Centres For RF Room Thermostats and Clocks	Pack Qty.	Code No.	Price Each £	
2 Zone Master Unit - Provides hard wired connections for Boiler, Zone Valve, UFH pump, power supply and Actuators (2 zone). Provides RF Connectivity for RF Clock and up to 2 RF Thermostats	1	PB2ZM RF	200.00	
4 Zone Slave Unit RF - Plug in connection to PB2ZM RF and provides RF connectivity for up to 4 Zones	1	PB4ZS RF	100.00	
RF Receiver - Remote RF receiver providing connectivity and to any RF Thermostat or time clock (switches 230V)	1	PB REC RF	45.00	

Wet Room Sensor	Pack Qty.	Code No.	Price Each £	
Includes 3m Sensor Cable - Connects to all wired and RF Room Thermostats for remote sensing in wet rooms	1	PB23020	12.10	

Room Temperature Controls

Room Packs

This range of underfloor heating packs contains all the flooring and control equipment required for a single room project. Please note that all Room Packs have a maximum output of 100W/m².

1. Select the floor type applicable for the room from the following options:

Solid Floor (Code So)
Overlay™ (Code O)
Overlay™ Lite (Code OL)

2. Select the total heated floor area for the room and round up to the following options:

Solid Floor	**Overlay™**	**Overlay™ Lite**
12m² (Code **12**)	5m² (Code **5**)	12m² (Code **12**)
20m² (Code **20**)	12m² (Code **12**)	20m² (Code **20**)
30m² (Code **30**)	20m² (Code **20**)	30m² (Code **30**)
	30m² (Code **30**)	

3. Add the control:

ZRU – For connection to existing heating (Code **Z**)
A dedicated Overlay™ Bathroom Pack (**O5B**) is available for rooms up to 5m². This is supplied with a temperature limiting valve for connection to existing heating systems, so no control method need be specified.

EXAMPLE:
The order code for a 12m² solid floor with a ZRU would be:

So	**12**	**Z**
Solid Floor	12m² Floor Area	Control Type

Pack Number	Floor Type	Area M²	Control Type	List Price Each £
Room Pack Availability	1	2	3	
O5B	Overlay™	5	Temp. Limiting Valve	310.00
O12Z	Overlay™	12	ZRU	859.00
O20Z	Overlay™	20	ZRU	1100.00
O30Z	Overlay™	30	ZRU	1421.00
OL12Z	Overlay™ Lite	12	ZRU	859.00
OL20Z	Overlay™ Lite	20	ZRU	1100.00
OL30Z	Overlay™ Lite	30	ZRU	1421.00
So12Z	Solid	12	ZRU	607.00
So20Z	Solid	20	ZRU	774.00
So30Z	Solid	30	ZRU	974.00

Room Packs	Pack Code	Pack Code	Pack Code	Pack Code
Overlay™ Single Room Packs	O5B	O12Z	O20Z	O30Z
Product	Qty	Qty	Qty	Qty
Overlay™ Temperature Limiting Valve	1			
Overlay™ Panel (Pack of 10)	1		1	
Overlay™ Panel (Pack of 30)		1	1	2
Overlay™ End Returns (Pack of 10)	1	2	4	6
Overlay™ Pipe (12mm x 80m)	1	1	2	3
Overlay™ Glue	1	1	2	2
12 x 15mm Adaptors (Pack of 2)	1	1	2	3
15mm PolyPlumb Tees			2	4
15mm PolyPlumb Spigot Elbows			2	4
ZRU (Zonal Regulation Unit)		1	1	1

Overlay™ Lite Single Room Packs	OL12Z	OL20Z	OL30Z
Product	Qty	Qty	Qty
Overlay™ Lite Panel (Pack of 10)		1	
Overlay™ Lite Panel (Pack of 20)	1	1	2
Overlay™ End Returns (Pack of 10)	2	4	6
Overlay™ Pipe (12mm x 80m)	1	2	3
Self Adhesive Aluminium Tape	1	2	2
12 x 15mm Adaptors (Pack of 2)	1	2	3
15mm PolyPlumb Tees		2	4
15mm PolyPlumb Spigot Elbows		2	4
ZRU (Zonal Regulation Unit)	1	1	1

Solid Floor Single Room Packs	So12Z	So20Z	So30Z
Product	Qty	Qty	Qty
Screeded Solid Floor Panels	12	20	30
15mm x 100m Pipe Coil	1	2	3
Edge Insulation	1	1	2
Pipe Stiffeners	1	1	1
15mm PolyPlumb Tees		2	4
15mm PolyPlumb Spigot Elbows		2	4
ZRU (Zonal Regulation Unit)	1	1	1

Room Temperature Controls

Renewable Pipe Systems

Polypipe offers a range of pre-insulated pipe systems, which provide flexibility, durability and availability when required.

These systems meet the growing demand for products that are suitable for renewable heat sources such as remote boilers and heat pumps. Installation is fast and easy, requiring just a single lay of the flow and return pipes, which are both contained in a single casing. The inner water bearing pipes are PEX barrier pipes, which are contained in a corrugated HDPE outer casing.

Polypipe pre-insulated pipes are fastened using brass mechanical clamp fittings, which require no special tools or equipment.

Pre-Insulated Pipes

Pipes (Twin Pipe Coil) Outside casing 160mm (OD) Bend radius 0.5m	Pack Qty.	Code No.	Price Each £
25mm x 10m, PE-Xa 2mm x 25mm (OD) 20 DN (ID)	1	INS1025-2-HTG	**404.98**
25mm x 15m, PE-Xa 2mm x 25mm (OD) 20 DN (ID)	1	INS1525-2-HTG	**607.48**
25mm x 20m, PE-Xa 2mm x 25mm (OD) 20 DN (ID)	1	INS2025-2-HTG	**809.95**
32mm x 10m, PE-Xa 2mm x 32mm (OD) 25 DN (ID)	1	INS1032-2-HTG	**477.11**
32mm x 15m, PE-Xa 2mm x 32mm (OD) 25 DN (ID)	1	INS1532-2-HTG	**715.67**
32mm x 20m, PE-Xa 2mm x 32mm (OD) 25 DN (ID)	1	INS2032-2-HTG	**954.23**

Max operating pressure: 6 bar. Max fluid temperature: +95°C. PE-Xa pipes: SDR 11. Carrier pipes are individually identified as flow and return.

Dust Cap	Pack Qty.	Code No.	Price Each £
160mm x 25mm Dust Cap	1	INS160-25-2DC	**10.37**
160mm x 25mm Dust Cap	1	INS160-32-2DC	**10.37**

Heat Shrink Cap	Pack Qty.	Code No.	Price Each £
160mm Heat Shrink Cap	1	INS160-3225-2HSC	**104.25**

Insulation Kit For Coupler	Pack Qty.	Code No.	Price Each £
160mm (OD) to fit outside casing, 1000mm (L) 180mm (OD)	1	INS160IKC	**84.45**

Kit comprises a smooth black HDPE pipe, rock wool insulation, 2 shrink sleeves, adhesive tape and assembly instructions. Heat shrinkable cap to be ordered separately.

Male Couplings For PEX pipe	Pack Qty.	Code No.	Price Each £
25mm (OD)/2.3 (w/t) thread ¾"	1	INS25MC-HTG	**24.68**
32mm (OD)/2.9 (w/t) thread 1"	1	INS32MC-HTG	**32.35**

Max operating pressure: 10 bar. Max fluid temperature: +95°C. PE-Xa pipes: SDR 11.

Female Couplings	Pack Qty.	Code No.	Price Each £
25mm, thread ¾"	1	INS25FC-HTG	**4.81**
32mm, thread 1"	1	INS32FC-HTG	**7.06**

Fix Points	Pack Qty.	Code No.	Price Each £
25mm, thread ¾" FF	1	INS25FP-HTG	**8.70**
32mm, thread 1" FF	1	INS32FP-HTG	**19.76**

Fix points must be installed to absorb the possible effects of thermal expansion/ shrinkage of the PE-Xa transport pipe. The non application of fixed points may result in serious damage to pipes, joints and buildings.

Standards & Polypipe Guarantee Information

Polypipe meets, and constantly strives to exceed, the changing laws and regulations governing our operations and products. We have invested in extensive testing and development facilities to ensure the products we supply are of the highest quality. Our plumbing systems conform to a number of 3rd party accredited standards which are listed below.

British Standard Class S rated to BS7291 Part 1 and Kitemark Licence Number 38148 to BS7291 Part 1 & 2

PolyPlumb polybutylene barrier pipe, fittings and accessories are covered by BBA Certificate No 00/3699

Listed in the WRAS Water Fittings and Materials Directory

Standards Manufacturing Quality Assurance - in accordance with BS EN ISO 9002 (BSI registered firm Certificate FM00318)

British Gas has accepted the Polypipe 'PolyPlumb' & 'PolyFit' Class S polybutylene pipe systems as being acceptable for open vented and sealed central heating systems and are eligible for acceptance onto Home Care Central Heating System Cover

At Polypipe we pride ourselves on offering the highest quality products, and wherever possible our products and processes are covered by independent third-party accreditation, so you can rest easy knowing that you are buying from the UK's market leading manufacturer. We have invested significantly in our quality control procedures, have our own fully-equipped modern laboratory for development and analysis, and also have our own tooling and extrusion processes.

P.B.P.S.A. - Polypipe Building Products is a member of the Polybutylene Piping Systems Association which is a recognised association of companies whose aim is to promote the features, benefits and best practice installation techniques of polybutylene pipe systems as well as providing a wide range of technical information and support. The P.B.P.S.A. web site can be found at www.PBPSA.com.

Installation Standard

Installation must follow the requirements of BS5955 - PART 8 2001 Plastic Pipework (Thermoplastic Materials).

Guarantee

Polypipe guarantees for 25 years against defects in materials or manufacture of the PolyPlumb, PolyMax, PolyFit and PolySure hot and cold water supply and heating systems from the date purchased. This guarantee only applies if the products are installed in accordance with the manufacturers recommendations and are used in a normal domestic operation.

A normal domestic operation is defined as a residential property and excludes commercially run residential properties e.g. care homes and is also defined as being part of an open vented or sealed central heating system, direct or indirect single pipe hot water supply or mains or tank fed cold water supply system.

The system must be designed, installed and operated within the temperature and pressure ratings as defined in BS 7291 Class S which are also published in the manufacturer's literature and must also take account of all the other exclusions and limitations as defined in the design, application and installation guidance provided by the manufacturer.

Exclusions apply, please contact the manufacturer for further details.

For Polypipes Contract of Sale, please refer to **www.polypipe.com**

Underfloor Heating Pipe (UFH) and MCP Underfloor Heating Pipe (MCP) - Application Classes

The Polypipe UFH and MCP underfloor heating pipes have been tested in accordance with BS EN ISO 15876-1:2003 and BS EN ISO 21003-1:2008 respectively at a maximum design pressure of 10 bar for application class 4 - **Underfloor heating and low-temperature radiators only**. The maximum operating temperature of these pipes is **60°C**.

These pipes are **NOT suitable for potable cold water or domestic hot water services**.

The following information is designed to provide basic guidance for installers and specifiers when selecting Polypipe products. The information is not exhaustive and guidance may change dependent on site conditions and applications. This document should be read in conjunction with the Polypipe Plumbing & Heating Product Guide. If in doubt please contact our Technical Services Department on **01709 770000**.

Service Conditions

Grey and White Plumbing and Heating Pipe, PolyPlumb, PolyMax, PolyFit and PolySure fittings are suitable for the following Class S service conditions in a normal domestic operation (subject to the exceptions referred to in note 2 below):

(Continuously operated ring main installations are excluded from these applications.)

	Nominal system flow temperature Tf °C (see explanatory note 1 below)	Maximum system service temperature Ts °C (see explanatory note 1 below)	System malfunction temperature Tm °C (see explanatory note 1 below)	System maximum working pressure bar
Indirect cold water systems	20	20	-	3½
Direct mains-fed cold water systems	20	20	-	12½
Subsurface heating systems (including Underfloor)	60	83	100	3½
Vented hot water supply systems	65	83	100	3½
Unvented hot water supply systems including instantaneous heaters and/or incorporating storage	65	95	100	6
Vented central heating systems	82	95	100	3½
Sealed central heating systems	82	105	114	3

Note 1:
- nominal system flow temperature Tf is the intended maximum flow temperature of a system for a particular application as recommended in codes of practice and other guidance documents
- maximum system service temperature Ts is the maximum service temperature that can occur intermittently during normal operation
- system malfunction temperature Tm is the maximum temperature likely to be applied to pipes and fittings in the event of control thermostat failure or malfunction

Note 2:
- certain fittings in the Polyplumb, PolyMax and PolyFit ranges are not suitable for all the Class S service conditions. The limitations are indicated against every applicable fitting in the Trade Price List e.g. "Cold Water Only".

Connections to other materials

Connection to Imperial Copper using PolyPlumb

Imperial ¾" copper pipe is of significantly different size to its metric 22mm counterpart and therefore requires a different 'O' ring to that supplied in the 22mm fitting. The 22mm 'O' ring should be replaced with a ¾" 'O' ring (PB9034). Standard 15mm fittings can be connected to Imperial ½" copper pipe, and 28mm fittings can be connected to 1" copper pipe.

Connection to Irish copper pipe

Irish copper pipe to IS238:1980 can be connected to PolyPlumb fittings which incorporate the ¾" or 1" adaptor set. Using a standard 22mm or 28mm PolyPlumb fitting, remove the nut and socket components and discard. Replace these parts with the relevant adaptor set, ¾" - PB7034 or 1" - PB701. The adaptor sets are distinguishable by the black cap nut.

Connections to chrome plated and stainless steel pipework

PolyPlumb, PolyFit and PolyMax fittings should not be connected directly to chrome plated copper pipes or stainless steel pipes. To connect to these pipes we recommend the use of a compression coupler. A pipe stiffener should be used when connecting Polypipe Grey and Polypipe White pipe to a compression fitting.

Connecting PolySure press fit fittings to copper

PolySure press fit fittings have been designed specifically to fit to Polypipe grey and Polypipe white polybutylene pipes. To connect to copper pipes we advise the use of a PolySure press fit x BSP male or female adaptor, with the corresponding adaptor being used on the copper side from the PolyPlumb or PolyFit range. PTFE tape should be used to seal the mating brass components.

Connections close to capillary fittings

Capillary fittings should preferably be completed prior to the use of Polypipe fittings. Where this is not possible, care should be taken to ensure that flux or solder does not come into contact with plastic pipes or fittings. A damp cloth should be wrapped around the copper pipe close to the nearest plastic pipe or fitting to ensure against damage by conductive heat. Pipework should be flushed to clear flux before active use.

Connections to incoming cold water supply

There are two options for connecting incoming MDPE mains water service pipe to Polypipe Plumbing and Heating Systems. Firstly the push fit x compression adaptors provide a one piece transition fitting covering connections from 20mm, 25mm and 32mm MDPE service pipes to 15mm, 22mm and 28mm polybutylene pipes and most sizes are available in both Polypipe Grey and White versions. Secondly, as there is a requirement for a stopcock on the incoming main there is also a combined stopcock and adaptor which reduces the number of fittings required in a position where there is often limited space e.g. under a kitchen sink. These products allow connections from 20mm or 25mm MDPE pipe via a compression end to 15mm or 22mm polybutylene using a push fit connection.

Gas, oil, and compressed air

Polypipe systems are suitable for domestic plumbing and heating systems. Pipes and fittings must not be used for gas and oil supply pipework or compressed air pipework. In all the above instances metal pipework should be installed.

Continuously operated re-circulating systems (Secondary Hot Water Circulation / Ring main installations)

A continuously operated re-circulating system is a water-replenished circulating system which is maintained at a constant high temperature to provide a constant source of hot water. Continuously operated re-circulating systems are used to distribute constant hot water to wards or rooms that may be distant from the heat source or hot water storage vessel. Locations where continuously operated re-circulating systems are used include, but are not limited to, residential care homes, hospitals and hotels. Continuously operated re-circulating systems are very different from conventional hot water supply and central heating systems found in domestic properties, for which our products have been tested to, under either BS 7291 Class S or WRAS approval standards, and for this reason PolyPlumb, PolyMax, PolyFit or PolySure must not be used on any continuously operated re-circulating systems. Some secondary hot water circulation systems are used intermittently, controlled by time and/or temperature thermostats. This application is also unsuitable for products manufactured to BS 7291.

Re-cycled rainwater systems

Polypipe products can be used in systems conveying re-cycled or harvested rainwater within domestic properties. All pipe work used in this type of system should be clearly identifiable and this should be carried out in accordance with WRAS Information and Guidance Note No 9-02-05; Marking and Identification of Pipework for Reclaimed (Greywater) Systems. If self adhesive labels are to be used, these should not be applied directly to the pipe.

Chlorine and other additives

The polybutylene material used in Polypipe Plumbing and Heating Systems is WRAS approved. It is resistant to the buildup of scale. Normal levels of chlorine in UK domestic water supplies will not have an adverse effect on Polypipe Plumbing and Heating Systems.

However Polypipe Plumbing and Heating Systems are not suitable for systems in which any further additives are ever added, periodically added, or regularly dosed in to or additional to the normal UK mains water supply, for example chlorine for swimming pools or those used for bacteria control or legionella prevention. Systems must not be flushed through with anything other than water from the normal UK mains water supply or a cleaning product at the correct concentration that is specifically recommended for plastic piping systems.

The use of corrosion inhibitor in central heating systems is acceptable provided that the inhibitor is specifically designed for plastic piping systems and guidance on their suitability should be sought from the inhibitor manufacturer prior to adding to the system.

Electrical Safety / Equipotential Bonding

Where Polypipe pipes break the continuity of existing metal pipe, which may be used for earthing, or bonding this continuity must be re-instated by affixing permanent earth clips and a section of earth cable between the copper ends on either side of the plastic sections. Both the IEE and the Chartered Institute of Plumbing and Heating Engineers now give guidance on the Earth Bonding requirements of Plastic Pipe systems. As plastic pipes do not conduct electricity, installations generally require less equipotential bonding than metal systems although if in doubt exact guidance should be sought.

Light

Polypipe Plumbing and Heating Systems should be protected from UV light. Standard decorating paints form adequate protection. Pipe insulation forms adequate protection for external use. Polypipe products are delivered in light protective packaging.

Compatibility with other substances

For details of compatibility with building and cleaning substances, and treatments (e.g. filler foam and wood worm treatments) please consult the relevant manufacturers to confirm suitability with Polybutylene. Polypipe Plumbing and Heating Systems pipes and fittings can be painted using emulsion or undercoat and gloss. Cellulose based paints, strippers or thinners must not be used.

Vermin

There is no evidence to suggest that Polypipe Plumbing and Heating Systems attract vermin. Where vermin are present they can cause damage to other services, building fabric and pipes and fittings, and therefore a qualified pest controller should be employed to remove vermin from the affected area.

Application Information

Connections to other equipment

Boilers and appliances:

All boilers and appliances must have safety devices such as thermostatic controls, cut-outs and pump over-run protection to make sure that they cannot operate above the Class S working temperature and pressure limits set out in the table of Class S service conditions above. Exposure to conditions in excess of those specified could result in failure of the pipes or fittings with the potential for serious injury.

Gas Boilers:

Pipe should only be connected to gas boilers where the pipe connection is outside the boiler casing and where the boiler incorporates a high limit thermostat and pump over-run facility. The pipe connections should be 350mm from the heat source. In all other situations, a section of metal pipe should be at least 1m in length. In addition for back boilers metal pipe work should be used within the fire opening extending out of the chimney brickwork.

Combination Boilers:

Where system connections are made to an incoming water supply pipe from a water meter or any other device which contains a check valve a suitable expansion vessel must be fitted to prevent the expansion of heated water back down the supply pipe. This is especially important where a water meter is fitted retrospectively.

Solid Fuel Boilers & Cooking Ranges

Pipes and fittings must not be used for primary or gravity circuits from solid fuel boilers, cooking ranges or other uncontrolled heat sources.

Solar Panels / Systems

Pipes and fittings must not be used for connection of solar panels or any part of solar distribution that operates above the Class S working temperature and pressure limits set out in the table of Class S service conditions above.

Oil Fired Boilers

Open Vented Central Heating Systems:

The use of plastic pipe and fittings is acceptable when used in oil fired installations where the boiler is connected to an open vented system, however the first metre of primary pipework from the boiler connections must be installed using metal pipe. The boiler must be suitable for this type of application and all relevant safety features as supplied and fitted to the boiler must be checked for correct operation. The system must also be commissioned in accordance with the boiler manufacturers instructions.

Plastic pipe and fittings can also be used in the hot and cold water and underfloor central heating systems with the exception of continuously operated re-circulating systems (see page 80) where plastic pipe and fittings should not be used.

For further information regarding the suitable applications for our plastic pipe and fittings please refer to the Class S Service Conditions table as shown on page 80 of this publication.

Sealed Central Heating Systems:

Where a sealed system oil fired boiler is to be used all primary boiler pipework to and from the hot water cylinder (if fitted) and any radiator or towel rail circuits must be installed using metal pipe and fittings.

Plastic pipes can be used on underfloor central heating systems where the plastic pipes are fitted after the UFCH control unit and manifold arrangement which must contain a correctly operating thermostatic mixing valve.

Plastic pipe and fittings can also be used in the hot and cold water system with the exception of continuously operated re-circulating systems (see page 80) where plastic pipe and fittings should not be used.

All relevant safety features as supplied and fitted to the boiler such as the boiler temperature control thermostat, high limit thermostat, pump overrun facility and the pressure and temperature relief valve must be checked for correct operation at both installation stage and at any subsequent boiler service intervals. The system must also be commissioned in accordance with the boiler manufacturers instructions.

For further information regarding the suitable applications for our plastic pipe and fittings please refer to the Class S Service Conditions table as shown on page 80 of this publication.

Use of aluminium tape

To comply with the NHBC guidelines regarding detection of pipes in wall cavities Polypipe recommends the use of aluminium tape. This tape should be applied directly to the wall sub-structure and pipes should be clipped on top of the tape. The tape must not be applied directly to the pipes.

"Dot and dab" walling

Dry lined or "dot and dab" walls are commonly used to speed up the build process and Polypipe systems are compatible with these types of constructions. Board adhesive or plaster should not be applied to Polypipe pipe and fittings especially around the area where the pipes pass through the wall to feed radiators and appliances. Pipes and fittings must remain accessible should future maintenance be required.

Handling and storage of products

The packaging of both pipes and fittings is designed to protect from ultraviolet light and environmental contamination. Pipes and fittings should therefore be retained in their packaging as long as possible, and should be stored in a cool dry area.

When on site, fittings should be stored to prevent dust and debris from entering the fitting and sticking to the pre-lubricated 'O' ring. Care should be taken to avoid scratching the pipe surface during the handling, storage and installation processes.

Insulation of pipework

If pipe and fittings are installed in an environment that is not heated or alternatively outside, they should be protected from potential frost damage in accordance with BS6700 and BS5422.

System testing

Pressure testing of the pipe system is essential however a successful pressure test using the following steps is not a guarantee of complete and correct installation and only ensures that pipes have been inserted into fittings passed both the 'O' ring and the grab ring. If pipes have been scored or scratched during the installation process a high pressure test as below may not highlight these issues.

1st fix Installations

Step 1:

Pipe and fittings only should be tested. The system should be filled completely using water not more than 20°C at a test pressure of 18 bar which should be applied for not less than 15 minutes and no longer than 1 hour. Joint security can be checked visually and by tugging at joints.

2nd fix Installations

Step 2:

Complete installations including appliances should be tested with water to the maximum pressure allowed by the manufacturers of the appliances and fittings. Please note, due to health and safety reasons pipework installations must not be air tested.

Pressure testing in sub zero temperatures

Special precautions are necessary if the pressure testing is to take place in sub-zero temperatures.

This applies particularly in underfloor central heating systems using the screeded floor system where most of the pipe is encased in concrete. Due to the contact between pipe and floor panel on screeded installations, where the screed does not completely surround the pipe, there may be points where strain is created on the pipe in freezing conditions which is not normally present.

Therefore it is advisable to drain the under floor central heating system once testing and screeding has been completed.

Precautions should also be taken where installations contain large quantities of fittings which due to the rigidity of their construction may put undue pressure on the pipe.

Polypipe
Plumbing & Heating
Trade Price List

Polypipe Ulster

Dromore Rd, Lurgan Craigavon, Co. Armagh, BT66 7HL, UK
T: +44 28 38 881270   F: +44 28 38 882344

Polypipe Building Products

2410 London Road, Mount Vernon, Glasgow, G32 8 XZ, UK
T: +44 141 778 8822   F: +44 141 778 2703

Polypipe Building Products

Broomhouse Lane, Edlington, Doncaster, DN12 1ES, UK
T: +44 1709 770000   F: +44 1709 770001