



TLM Room Thermostats



- 20 Amp rated On/Off contacts
- High specification and reliability
- Wide range available to suit all applications
- Robust magnetically controlled switch mechanism
- Adjustable Range Stops
- Tamperproof Models

The Sunvic TLM Room Thermostat is renowned for its high Specification and reputation for accuracy and reliability and is suitable for medium to heavy duty applications with a rating from 4 amp to 20 amp resistive loads (where rating does not exceed 6 amps the TLX Thermostat should be used). They incorporate a single pole, single throw (On/Off) switch and a robust magnetically controlled switching mechanism. The TLM Thermostats are available for applications including frost protection, underfloor heating and control of any direct electrical heating system.

TLM Room Thermostats are supplied with a steel base plate which is suitable for surface mounting or will fit to standard conduit boxes.

Type
Scale
Operating Voltages
Current Rating
Switch Type
Typical Applications

TLM2253
3° to 27°C
220/240Vac
16 Amp
SPST
Standard thermostat to control any direct electrical heating system

TLM2257
-15° to +10°C
220/240Vac
16 Amp
SPST
Frost Thermostat to protect heating systems, machinery etc. from low temperature damage.

TLM2402
3° to 27°C

220/240Vac

20 Amp

SPST

Standard model with non-ventilated concealed setting case to protect against dust etc and to prevent unauthorised adjustment.

TLM2453

3° to 27°C

220/240Vac

16 Amp

SPST

Standard model with tamperproof case (complete with shear off screws) to prevent unauthorised adjustment. For use in public buildings, schools etc

TLM2628

3° to 27°C

220/240Vac

20 Amp

SPST

Standard model with indicated OFF position. For use when a positive switch is required

TLM2655

0° to 15°C

220/240Vac

20 Amp

SPST

Standard Model 0°C night set back facility - to provide auto set back when used with time clock or switch

TLM2802

10° to 40°C

220/240Vac

20/5 Amp

SPDT

Standard thermostat with changeover back contact with rating 5amp resistive

836-2405

BX3

Optional Accessory

837-1203

Guard Pack

Optional Accessory