

- System Specification -**for PROGEF Standard Piping Systems in Polypropylene (PP)****1. Scope**

This specification covers the requirements for the Georg Fischer **PROGEF Standard (PP)** Piping System intended for a wide range of applications including water, wastewater and effluent treatment as well as a wide range of chemical applications. The components of the **PROGEF Standard (PP)** piping system are in accordance with the following standards.

2. Basic System Data**2.1 Material Specification for PROGEF Standard (PP) System**

All **PROGEF Standard (PP)** pipes, fittings and valves from Georg Fischer Piping Systems are manufactured either from isotactic Polypropylene Homopolymeride **β-PP-H** or from Polypropylene random co-polymeride **PP-R** with a value of MRS 10 MPa, of which pipes and fittings are designed for 25 years operational life with water at 20°C. The material is designed for use with pressure bearing piping systems with long-term hydrostatic properties in accordance with EN ISO 15494, as supplied by Georg Fischer Piping Systems.

2.1 Characteristics of PROGEF Standard (PP) Material

Characteristics	β-PP-H	PP-R	Units	Standard
Density	0.90-0.91		g/cm ³	EN ISO 1183-1
Yield stress at 23°C	31	25	N/mm ²	EN ISO 527-1
Flexural E-Modulus at 23°C	1300	900	N/mm ²	EN ISO 527-1
Charpy notched impact strength at 23°C	85	30.9	kJ/m ²	EN ISO 179-1/1eA
Charpy notched impact strength at 0°C	4.8	3.4	kJ/m ²	EN ISO 179-1/1eA
Ball indentation hardness (132N)	58	49	MPa	EN ISO 2039-1
Heat distortion temperature HDT B 0,45 MPa	95	75	°C	EN ISO 75-2
Crystallite melting point	150-167	145-150	°C	DIN 51007
Thermal expansion coefficient	0.16...0.18		mm/mK	DIN 53752
Heat conductivity at 23°C	0.23		W/mK	EN 12664
Water absorption at 23°C	0.1		%	EN ISO 62
Colour	neutral	7032	RAL	RAL
Limiting oxygen index (LOI)	19		%	ISO4589-1

- System Specification -

2.2 PROGEF Standard (PP) Product Range

Products	SDR	PII	d16 DH10	d20 DH15	d25 DH 20	d32 DH25	d40 DH32	d50 DH40	d63 DH50	d75 DH65	d90 DH80	d110 DH100	d125 DH100	d140 DH125	d160 DH150	d180 DH150	d200 DH200	d225 DH200	d250 DH250	d280 DH250	d315 DH300	d355 DH350	d400 DH400	d450 DH450	d450 DH500	d500 DH500	d560 DH600	d630 DH600
Pipes	7.4	16																										
	11	10																										
	17.6	6																										
Socket fusion fittings	11	10																										
Butt fusion fittings, infrared (IR) compatible	11	10																										
	17.6	6																										
Ball valves	11	10																										
	17.6	6																										
Diaphragm valves	11	10																										
	17.6	6																										
Butterfly valves	-	10																										
Control valves	-	-																										
Pressure regulating valve	-	-																										
Ventilating and Bleed valves	-	-																										
Measurement and control	-	-																										
Flange PP-Y / PP-steel	-	-																										
Flange seal	-	-																										
Welding machines and assembly	-	-																										

available

For more technical information, please see the Georg Fischer Piping Systems Planning Fundamentals on the +GF+ website (www.piping.georgfischer.com).

2.3 Approvals / Acceptance / Conformance

This **PROGEF Standard (PP)** material specification is met the directives of Georg Fischer Piping Systems. Therefore Georg Fischer Piping Systems is approved according to the different categories all over the world. For more information please see our approvals database on the +GF+ website.

	FDA	USP 25 class VI	DIBt	GOST-R	CE	DNV	Lloyd's register	RINA	BV
							Shipbuilding		
Raw material									
Pipe									
Fittings									
Valves									
Backing Flanges									
Gaskets									

available

- System Specification -

3. Pipes

PROGEF Standard (PP) pipes are made of **β-PP-H** and comply with a MRS class of 10. Processing of pipes is done according to EN ISO 15494, DIN 8077 (dimensions) and DIN 8078 (quality specifications).

Outer diameter, ovality and wall thickness are defined according to Tables 1 - 3.

Table 1: Measurements SDR 7.4

In millimeters

Nominal outer diameter	Min. wall thickness	Tolerance limit of outer diameter	Maximum deviation for ovality	Tolerance limit of wall thickness	Pipe series	Nominal pressure
d_n	e_{min}			a	S	PN
16	2.2	+ 0.3	0.3	+ 0.5	3.2	16
20	2.8	+ 0.3	0.3	+ 0.5	3.2	16
25	3.5	+ 0.3	0.4	+ 0.6	3.2	16

a Tolerance limit of wall thickness: $0.1e + 0.2$ mm, rounded to 0.1 mm

Maximum deviation for ovality: $0.015 d_n$, rounded to 0.1 mm

Table 2: Measurements SDR 11

In millimetres

Nominal outer diameter	Min. wall thickness	Tolerance limit of outer diameter ¹	Maximum deviation for ovality	Tolerance limit of wall thickness	Pipe series	Nominal pressure
d_n	e_{min}			a	S	PN
16	1.8	+ 0.3	0.3	+ 0.4	5	10
20	1.9	+ 0.3	0.3	+ 0.4	5	10
25	2.3	+ 0.3	0.4	+ 0.5	5	10
32	2.9	+ 0.3	0.5	+ 0.5	5	10
40	3.7	+ 0.3	0.6	+ 0.6	5	10
50	4.6	+ 0.3	0.8	+ 0.7	5	10
63	5.8	+ 0.4	1.0	+ 0.8	5	10
75	6.8	+ 0.4	1.2	+ 0.9	5	10
90	8.2	+ 0.4	1.4	+ 1.1	5	10
110	10.0	+ 0.4	1.7	+ 1.2	5	10
125	11.4	+ 0.4	1.9	+ 1.4	5	10
140	12.7	+ 1.3	2.1	+ 1.5	5	10
160	14.6	+ 1.5	2.4	+ 1.7	5	10
180	16.4	+ 1.7	2.7	+ 1.9	5	10
200	18.2	+ 1.8	3.0	+ 2.1	5	10
225	20.5	+ 2.1	3.4	+ 2.3	5	10
250	22.7	+ 2.3	3.8	+ 2.5	5	10
280	25.4	+ 2.5	4.2	+ 2.8	5	10
315	28.6	+ 2.5	4.8	+ 3.1	5	10
355	32.2	+ 3.2	5.4	+ 3.5	5	10
400	36.3	+ 3.6	6.0	+ 3.9	5	10
450	40.9	+ 3.8	15.8	+ 4.3	5	10
500	45.4	+ 4.0	17.5	+ 4.8	5	10

¹ d16 – d125 suitable for socket-, butt and electrofusion welding technologies

d140 – d500 suitable for butt- and electrofusion welding technologies

- System Specification -

Table 3: Measurements SDR 17.6

In millimetres

Nominal outer diameter	Min. wall thickness	Tolerance limit of outer diameter ¹	Maximum deviation for ovality	Tolerance limit of wall thickness	Pipe series	Nominal pressure
d_n	e_{min}			a	S	PN
50	2.9	+ 0.3	0.8	+ 0.5	8.3	6
63	3.6	+ 0.3	1.0	+ 0.6	8.3	6
75	4.3	+ 0.4	1.2	+ 0.7	8.3	6
90	5.1	+ 0.4	1.4	+ 0.8	8.3	6
110	6.3	+ 0.4	1.7	+ 0.9	8.3	6
125	7.1	+ 0.4	1.9	+ 1.0	8.3	6
140	8.0	+ 1.3	2.1	+ 1.1	8.3	6
160	9.1	+ 1.5	2.4	+ 1.2	8.3	6
180	10.2	+ 1.7	2.7	+ 1.3	8.3	6
200	11.4	+ 1.8	3.0	+ 1.4	8.3	6
225	12.8	+ 2.1	3.4	+ 1.5	8.3	6
250	14.2	+ 2.3	3.8	+ 1.7	8.3	6
280	15.9	+ 2.5	4.2	+ 1.8	8.3	6
315	17.9	+ 2.5	4.8	+ 2.0	8.3	6
355	20.1	+ 3.2	5.4	+ 2.3	8.3	6
400	22.7	+ 3.6	6.0	+ 2.5	8.3	6
450	25.5	+ 3.8	15.8	+ 2.8	8.3	6
500	28.4	+ 4.0	17.5	+ 3.1	8.3	6

The mean outer diameter (d_{em}) is the average value which results from the measurements of the outer diameter at an interval of d_n and $0.1 d_n$ to the end of the test piece. It is determined by measuring the circumference to 0.1 mm accuracy with a measuring tape.

The minimum and maximum wall thickness is determined to 0.1 mm, whereby the measurement points should be distributed on the pipe circumference as evenly as possible. Individual exceedances of the pipe wall thickness may be

for $e \leq 10 \text{ mm}$ + 0.2 mm
 and for $e > 10 \text{ mm}$ + 0.15 e .

The mean value of the wall thickness must be within the allowable tolerance limit. Smaller wall thicknesses are not allowed.

Ovality is the difference between the measured maximum and the measured minimum external diameter (d_e) at the same cross-section. It is calculated to 0.1 mm and measured immediately after production. The ovality requirement applies to the timepoint of manufacture.

- System Specification -

Approved pipes comply with the corresponding quality specifications of DIN Certco ZP A.9.4.1.


Pipe material has been designed for industrial service and an enhanced chemical resistance (esp. at elevated temperatures) based on modified thermo-stabilizer package used. The chemical resistance comply with the DIBt-list as a minimum.

3.1 Product Marking

All pipes must be marked permanently and consecutively at intervals of at least 1 meter.

- Material identification: +GF+ manufacturing plant identification **PROGEF**
- Material code: PP-H 100
- Pipe diameter, wall thickness, SDR and PN: see Tables 1 - 3
- RAL symbol and Z-40.23-4 (DIBt)
- Manufacture date, shift and machine number
- Product norm: DIN 8077/78

Example of marking :

PROGEF +GF+  DEKAPROP PP-H 100 63 x 5.8 DIN 8077/78 PN 10 SDR 11
Manufacture date Shift Machine no. RAL symbol 006 Z-40.23-4 Ü

The marking shall be done by hot embossing and a yellow coding tape. Marking is also possible with an inkjet device.

- System Specification -

4. Fittings

All **PROGEF Standard (PP)** fittings are either as butt fusion type, metric sizes d20 – 500 mm, or socket fusion type, metric sizes d16 – 110 mm, labelled with +GF+. The dimensions of both fitting types fulfil the tolerance requirements of the standard EN ISO 15494. They need to be tested according to EN 10204. All threaded connections have pipe threads in accordance with the requirements of ISO 7-1.

PROGEF Standard (PP) fittings from d16 – 225 mm are manufactured from isotactic Polypropylene Homopolymeride **β-PP-H**. Fittings from d250 – 500 mm are manufactured either from isotactic Polypropylene Homopolymeride **β-PP-H** or from Polypropylene random co-polymeride **PP-R**.

All butt fusion spigot fittings of the dimension d20 – 225 mm are manufactured with laying lengths designed for use with the fusion machine IR-63 Plus, IR-110 Plus and IR-225 Plus from Georg Fischer Piping Systems.

4.1 Product Marking

Each part is marked according to EN ISO15494:

- Logo of manufacturer
- SDR-rating
- The PN rating
- Dimension (without the letter “d”)
- Material
- Permanently embossed date indicating the year and the production series.

4.2 Packaging and Labelling

The packaging must ensure that the fittings are not damaged during transportation.

Packaging and labelling must meet the following requirements:

- Identification of the content, in type, quantity and product details
- Information about standards and approvals covered by the product
- Content of the label has to accomplish legal requirements
- Labels must be EAN coded for automatic identification
- Comply to GF standards as well as to international standards such as ISPM15

- System Specification -**5. Accessories****5.1 Flanges**

Backing flanges in metric sizes DN 15-400 mm shall be designed according to EN ISO 15494, in a thermo plastic-oriented design, consisting of 100% glass fibre reinforced polypropylene, PP-GF30, graphite black and UV stabilized. These flanges are manufactured in a seamless technology injection moulding process by Georg Fischer Piping Systems. The backing flange shall be optimised with a V-groove in the inner diameter to ensure an evenly distributed force on the thermo plastic flange adapter. The backing flanges shall be marked with dimension, PN-value, standards, brand and lot number. Connecting dimensions metric according to ISO 7005, EN 1092; Bolt circle diameter PN 10; Inch: ANSI B 16.5, BS 1560; class 150 (1/2" – 12").

As an alternative backing flanges in metric sizes DN15-600 mm shall be designed according to EN ISO 15494, in a thermo plastic-oriented design, consisting of glass fibre reinforced polypropylene, PP-GF30, graphite black and UV stabilized with steel or cast inserts. The backing flanges shall be marked with dimension, PN-value, standards, brand and lot number. Connecting dimensions metric according to ISO 7005, EN 1092; Bolt circle diameter PN 10 (DN15-600mm) + PN16 (DN15-400mm); Inch: ANSI B 16.5, BS 1560; class 150 (1/2" – 8").

5.2 Gaskets

Gaskets in metric sizes DN10 – 600 shall consist of elastomeric material according to EN681, designed with or without metal reinforcement for use with flange adaptors according to EN ISO 15493. Gaskets with reinforcement shall be designed to be centred by the outer diameter. Gaskets with reinforcement shall provide fixation aids to fit on the flange bolts.

5.3 Pipe Support System

Pipe Support System shall be KLIP-IT, sizes d10-400 mm, supplied by Georg Fischer Piping Systems.

- System Specification -

6. Valves

All **PROGEF Standard (PP)** valves shall be metric sizes manufactured by Georg Fischer Piping Systems or equal in accordance with EN ISO 16135, 16136, 16137, 16138, tested according to the same standard.

6.1 Ball Valves

All **PROGEF Standard (PP)** ball valves with metric sizes DN 15 - 100 mm, shall be Georg Fischer Piping Systems Type 546, 543, 523 with true double union design manufactured by Georg Fischer Piping Systems in accordance with EN ISO 16135. Incorporated into its design shall be a safety stem with a predetermined breaking point above the bottom O-ring, preventing any media leaking in the event of damage. The valve nut threads shall be buttress type to allow fast and safe radial mounting and dismounting of the valve during installation or maintenance work. Seats shall be PTFE with backing rings creating self-adjusting seals and constant operating torque. Backing rings and seals shall be EPDM or FPM. The handle shall include in its design an integrated tool for removal of the union bush. Union bushes shall have left-hand threads to prevent possible unscrewing when threaded end connectors are removed from pipe.

Following accessories shall be available:

- A Multi-Functional Model (MFM) in PPGF equipped with internal limit switches for reliable electrical position feedback, is mounted directly between the valve body and the valve handle. This MFM is also the necessary interface for later mounting of actuators.
- Mounting plate in PPGF with integrated inserts for later screw mounting on any support
- Lockable multi-functional handle

- System Specification -

6.1.1 Electrically Actuated Ball Valves

Electric actuators shall be Types EA11 (sizes DN 10-50 mm), EA21 (sizes DN10-50 mm), EA31 (sizes DN 65-100 mm) shall be available manufactured by Georg Fischer Piping Systems in accordance with EN 61010-1, EC directives 2004/108/EC (EMC) and 2006/95/EC, LVD and needs to be **CE** marked. Actuator housing shall be made of PPGF (polypropylene glass fibre reinforced), flame retardant with external stainless steel screws. All electric actuators shall have an integrated emergency manual override and integrated optical position indication. All electric actuator types (with the exception of EA11) shall have the following accessories available:

- Fail-safe unit
- Heating element
- Cycle extension, cycle time monitoring, and cycle counting
- Motor current monitoring
- Position signalisation
- Positioner Type PE25
- Limit switch kits Ag-Ni, Au, NPN, PNP, NAMUR
- AS Interface Plug Module

Electric actuator specifications of the actuators shall be as follows:

Specification	EA11	EA21	EA31	EA42
Nominal torque (Nm)	10	10	60	100
Control time (s/90°)*	5	5	15	25
Cycles at 20°C *	150,000	250,000	100,000	75,000
Duty cycles ED at 20°C	40%	100%	50%	35%
Protection class	IP65 per EN 60529 - IP67 (for vertical cable mounting and wall feed through).			
Voltage	100-230, 50-60 Hz or 24V=24V, 50/60 Hz versions			

* = at nominal torque

6.1.2 Pneumatically Actuated Ball Valves

Pneumatic actuators shall be Georg Fischer Piping Systems Types PA11 (for valve sizes DN 15-25 mm) and PA21 (for valve sizes DN 32-50 mm). They shall be manufactured by Georg Fischer Piping Systems. Pneumatic actuators shall be available as fail safe close, fail safe open and double acting and have an integrated optical position indication. Actuator housing shall be made of Polypropylene fibre glass reinforced (PPGF) and flame retardant. Actuators shall contain a preloaded spring assembly to ensure safe actuator operation and maintenance. Actuators shall contain integrated Namur interface for the easy mounting of positioners, limit switches and accessories. The valve shall be equipped with a Multi-functional-module for reliable electric feedback, mounted directly between the valve body and the actuator as manufactured by Georg Fischer Piping Systems.

- System Specification -

- For valve size DN 65 mm pneumatic actuators shall be Type PA 30 (fail safe to close or open function), Type PA35 (double acting function).
- For valve size DN 80 mm pneumatic actuators shall be Type PA 35 (fail safe to close or open function), Type PA40 (double acting function).
- For valve size DN 100 mm pneumatic actuators shall be Type PA 45 (fail safe to close or open function), Type PA45 (double acting function)

Pneumatic actuators shall have an integrated optical position indicator. Actuator housing shall be made of hardened anodized aluminium. Actuators shall contain integrated Namur interface for the easy mounting of positioners, limit switches and accessories.

All pneumatically actuated ball valves shall have the following accessories available:

- Pilot valve remote or direct mounted in voltages 24VDC/AC, 110VAC, 230VAC
- Positioner Type DSR 500-3
- Limit switch kits Ag-Ni, Au, NPN, PNP
- Stroke limiter
- Manual override for all sizes up to d 110 mm
- AS Interface control module with incorporated position feedback and a solenoid pilot valve

- System Specification -

6.2 Diaphragm Valves

6.2.1 Manual Diaphragm Valves

6.2.1.1 Diaphragm Valves DN15 to DN50

All **PROGEF Standard (PP)** diaphragm Valves, metric sized from d20 to d63, shall be either:

- Type 514 (true double union design, DN15 to 50), or
- Type 515 (spigot design, DN15 to 50), or
- Type 517 (flange design, DN15 to 50), or
- Type 519 (T-type design, DN15-15 to 50-25)

All diaphragm Valves shall be manufactured by Georg Fischer Piping Systems in accordance with EN ISO 16138. The upper body shall be PPGF (polypropylene glass fibre reinforced) connected to the lower body with a central union avoiding exposed screws.

A two colored position indicator integrated into the hand wheel must be present to determine diaphragm position. The hand wheel shall have an integrated locking mechanism.

Diaphragms are to be EPDM, FPM, NBR, PTFE with EPDM or FOM supporting diaphragm. Following options shall be available:

- Electrical feedback unit with either AgNi or AU contacts
- Pressure proof housing

The diaphragm valve shall have following KV values:

d [mm]	DN [mm]	KV [l/min @ $\Delta P=1$ bar]
20	15	125
25	20	271
32	25	481
40	32	759
50	40	1263
63	50	1728

6.2.1.2 Diaphragm Valves DN65 to DN150

All **PROGEF Standard (PP)** diaphragm valves, metric sized, shall be Type 317 (flanged design, DN 65-150).

All diaphragm valves shall be manufactured by Georg Fischer Piping Systems in accordance with EN ISO 16138. The upper body shall be PPGF (polypropylene glass

- System Specification -

fibre reinforced) connected to the lower body with exposed stainless steel bolts. A position indicator integrated into the hand wheel must be present to determine diaphragm position. Diaphragms are to be EPDM, FPM, NBR, or PTFE with EPDM or FPM supporting diaphragm.

6.2.2 Pneumatic Diaphragm Valves

6.2.2.1 Pneumatic Diaphragm Valves DN15 to DN50

All **PROGEF Standard (PP)** diaphragm Valves, metric sized from DN15 to DN50, shall be either:

- true double union design, DN15 to 50, or
- spigot design, DN15 to 50, or
- flange design, DN15 to 50
- T-type design, DN15-15 to DN50-25

All diaphragm Valves shall be manufactured by Georg Fischer Piping Systems in accordance with EN ISO 16138. The upper body shall be connected to the lower body with a central union avoiding exposed screws.

Diaphragms are to be EPDM, FPM, NBR, PTFE with EPDM or FOM supporting diaphragm. Following options shall be available:

The diaphragm valve shall have following KV values:

d [mm]	DN [mm]	KV [l/min @ $\Delta P=1$ bar]
20	15	125
25	20	271
32	25	481
40	32	759
50	40	1263 (960*)
63	50	1728 (1181*)

*DIASTAR Six

Pneumatic actuators shall be Georg Fischer Piping Systems Type DIASTAR and shall be available as

- DIASTAR Six for PN up to 6 bar,
- DIASTAR Ten for PN up to 10 bar,
- DIASTAR Sixteen for PN up to 16 bar

The mode of operation shall be fail safe close (FC), fail safe open (FO) and double acting (DA). The valves shall have an integrated optical position indicator. Actuator housing shall be made of PPGF (polypropylene glass fibre reinforced). Actuators with

- System Specification -

FC mode shall contain a preloaded galvanised steel spring assembly to ensure safe actuator operation and maintenance. The actuator DIASTAR Ten and DIASTAR Sixteen shall have following accessories available:

- Solenoid pilot valve remote or direct mounted in voltages 24VDC/AC, 110VAC, 230VAC
- Positioner Type DSR 500-1
- Feedback with following limit switches Ag-Ni, Au, NPN, PNP, NAMUR
- Stroke limiter & emergency manual override
- ASI controller

6.2.2 Pneumatic Diaphragm Valves DN65 to DN150

All **PROGEF Standard (PP)** diaphragm valves, metric sized, shall be flanged design, DN 65-150.

All diaphragm valves shall be manufactured by Georg Fischer Piping Systems in accordance with EN ISO 16138. The upper body shall be connected to the lower body with exposed stainless steel bolts. Diaphragms are to be EPDM, FPM, NBR, or PTFE with EPDM or FPM supporting diaphragm.

Pneumatic diaphragm actuators shall be Georg Fischer Piping Systems Type DIASTAR Type 025. The mode of operation shall be fail safe close (FC), fail safe open (FO) and double acting (DA). The valves shall have an integrated optical position indicator. Actuator housing shall be made of PPGF (polypropylene glass fibre reinforced). Actuators with FC mode shall contain a preloaded galvanised steel spring assembly to ensure safe actuator operation and maintenance. The actuator DIASTAR 025 shall have following accessories available:

- Solenoid pilot valve remote or direct mounted in voltages 24VDC/AC, 110VAC, 230VAC
- Positioner Type DSR 500-2
- Feedback with following limit switches Ag-Ni, Au, NPN, PNP, NAMUR
- Stroke limiter & emergency manual override
- ASI Controller

- System Specification -

6.3. Butterfly Valves

All **PROGEF Standard (PP)** butterfly valves, metric sizes DN 50 (2") – 600 (24") mm, shall be Georg Fischer Piping Systems Type 567/568/563 wafer/lug type with a double eccentric disc design manufactured by Georg Fischer Piping Systems in accordance with EN ISO 16136. Seals shall be available in both EPDM and FPM. The lever handle shall be lockable in increments of 5 degrees. There shall always be six teeth engaged between the ratchet and the index plate to ensure accurate and safe positioning of the lever. There shall be the option of fine adjustment by use of a specific hand lever, allowing the disc to be exposed at any angle between 0° und 90°. As an option, the hand lever shall be lockable. The hand lever shall be manufactured of high strength PPGF (polypropylene glass fibre reinforced). The option of an integrated electric position indicator shall be available. Optional the valves can be actuated by gear box with hand wheel. The electric position indicator shall be integrated into the mounting flange. Butterfly valves shall have low actuation torque to enable easy operation. All butterfly valves Type 567 manufactured by Georg Fischer Piping Systems are designed for a nominal pressure rate of 10 bar. All butterfly valves Type 563 are designed for a nominal pressure rate of 4 bar.

6.3.1. Electrically Actuated Butterfly Valves

Electric actuators shall be Georg Fischer Piping Systems Types EA31 or EA42 dependent on valve size. They shall be manufactured by Georg Fischer Piping Systems in accordance with EN 61010-1, as per the above specifications. Actuator housing shall be made of PPGF (polypropylene glass fibre reinforced), flame retardant and feature external stainless steel screws. All electric actuators shall have an integrated emergency manual override and integrated optical position indication. All electric actuator types shall have the following accessories available:

- Fail-safe unit
- Heating element
- Cycle extension, monitoring, and counting
- Motor current monitoring
- Position signalisation
- Positioner Type PE25
- Limit switch kits Ag-Ni, Au, NPN, PNP
- Manual override
- AS-Interface Plug Modul

- System Specification -

6.3.2. Pneumatically Actuated Butterfly Valves

Pneumatic actuators shall be Georg Fischer Piping Systems Types PA 35 (metric sizes DN 50-65 mm), PA40 (metric size DN 80 mm only), PA45 (metric size DN 100 - 125 mm), PA55 (metric size DN 150-200 mm), PA60 (metric sizes DN 200mm FC), PA65 (metric sizes DN 250 mm FC) PA70 (metric sizes DN 300 mm FC). They shall be supplied by Georg Fischer Piping Systems. Pneumatic actuators shall be available as fail safe close, fail safe open and double acting and have an integrated optical position indication. Actuator housing shall be made of hardened anodized aluminium. Actuators shall contain integrated Namur interfaces for the easy mounting of positioners, limit switches and accessories. All pneumatically actuated butterfly valves shall have the following accessories available:

- Solenoid pilot valve remote or direct mounted in voltages 24VDC/AC, 110VAC, 230VAC
- Positioner Type DSR 500-3
- Feedback with following limit switches Ag-Ni, Au, NPN, PNP, NAMUR
- Stroke limiter & emergency manual override
- ASI-controller

- System Specification -

6.4 Check Valves

All **PROGEF Standard (PP)** cone check valves, according to EN ISO 16137, metric sizes DN 10-100 mm metric, shall be Type 561/562 true double union design. Seals shall be EPDM or FPM. Union bushes shall have a left hand thread to prevent possible unscrewing when threaded end connectors are removed from pipe. This valve shall be suitable for mounting in a vertical and horizontal position. Type 562 shall be equipped with a spring made of stainless steel (V2A) to allow position independent installation. The valves are designed for a nominal pressure of 10 bar.

6.4.1 Wafer Check Valves

All **PROGEF Standard (PP)** Wafer Check Valves shall be Georg Fischer Piping Systems Type 369, metric size DN 32-300 mm. The minimum water column of 2 m is required for sealing. They have to be equipped with a spring (either in 316 stainless steel or Hasteloy C) guaranteeing closing in all installation positions. Attention: A stabilizing pipe zone of at least 5 times nominal diameter (DN) (recommended 10 times nominal diameter) before and after the wafer check valve should be provided. The Wafer Check Valves manufactured by Georg Fischer Piping Systems are designed for a nominal pressure rate of 6 bar.

6.5 Pressure Regulating Valves

All **PROGEF Standard (PP)** pressure regulating valves as supplied by Georg Fischer Piping Systems shall have the following characteristics:

Pressure ranges for all pressure regulating valves are the following:

- DN 10 – 50 from 0 up to max. 10 bar
- DN 65 – 80 from 0 up to max. 6 bar
- DN 100 from 0 up to max. 4 bar

6.5.1 Pressure Reducing Valves

as supplied by Georg Fischer Piping Systems reduces the pressure within the system to a pre-set value. By using the differential pressure, the pressure reducing valve adjusts itself to the set working pressure. The outlet pressure (working pressure) is not directly related to the inlet pressure. If the outlet pressure increases above the set value, the diaphragm is lifted against the spring force. If the outlet pressure falls below the set value, the diaphragm is pressed down by the spring force. The pressure reducing valve begins to close/open until a state of equilibrium is re-established; in other words, the outlet pressure remains constant irrespective of an increasing or decreasing inlet pressure. Following types and sizes are available:

- Type V82, compact Pressure Reducing Valve with an integrated manometer, sizes DN 10 -100 mm

- System Specification -

- Type V182, compact Pressure Reducing Valve offering easy adjustment and real time visual control of the actual pressure reduction on the integrated manometer, sizes DN 10-40 mm
- Type V782, compact Pressure Reducing Valve, offering an easy adjustment, excellent flow rate and very low hysteresis, sizes DN 10-40 mm

6.5.2 Pressure Relief Valves

as supplied by Georg Fischer Piping Systems serves to keep the working or system pressures constant, to balance out pressure pulsation, and to reduce pressure peaks in process systems. The third pipe spigot fitted on the valve body means the valve can be installed directly in the main pipeline. If the inlet pressure rises above the set value, the pressurized valve piston is lifted against the spring force. Consequently, the valve opens and there is a reduction of pressure in the outlet pipe. The excess pressure can exhaust or be redirected via the third outlet. The valve closes as soon as the inlet pressure sinks below the pre-set spring tension. Following types and sizes are available:

- Type V185, Pressure Relief Valve, sizes DN 10-50 mm
- Type V85, Pressure Relief Valve, sizes DN 65 -100 mm

6.5.3 Pressure Retaining Valves

as supplied by Georg Fischer Piping Systems serves to keep the working or system related pressures constant, to balance out pressure pulsation, and to reduce pressure peaks in chemical process systems. If the inlet pressure rises above the set value, the pressurized valve piston is lifted against the spring force. Consequently, the valve opens and there is a reduction of pressure through the outlet pipe. The valve closes as soon as the inlet pressure sinks below the pre-set spring tension. Following types and sizes are available:

- Type V186, Pressure Retaining Valve, sizes DN 10-50 mm
- Type V86, Pressure Retaining Valve, sizes DN 65-100 mm
- Type V786, Pressure Retaining Valve, sizes DN 10-40 mm

6.6 Direct-acting Solenoid Valves

Supplied by Georg Fischer Piping Systems serves to regulate and control fluids, if no compressed air is available or not wanted. They are used for diverse functions, e.g. opening, shutting, dosing, distribute and mixing. The medium flow is switched directly by the armature moved by the magnetic force.

- Safety position shall be available

- System Specification -

Following type and sizes are available:

- Type 166, sizes DN3-5

6.7 Servo-assisted Solenoid Valves

Supplied by Georg Fischer Piping Systems serves to regulate and control fluids, if no compressed air is available or not wanted. They are used for diverse functions, e.g. opening, shutting, dosing, distribute and mixing. Opening large orifices using the direct-acting method would require enormous and expensive coils. Servo assisted valves use the power of the fluid to open the flow channel by controlling a small pilot channel to alter the forces on a larger main seal. A Δp of 0.5 bar is mandatory with servo-assisted valves.

- Type, 165, sizes DN10-50

6.8 Ventilating- and Bleed Valves

All **PROGEF Standard (PP)** Ventilating- and Bleed valves shall be Georg Fischer type 591. Dimensions DN10-100 are with pressure rating PN10. They shall be equipped with a PP-H floater with density of 0,91 g/cm³.

6.9 Ventilating Valves

All **PROGEF Standard (PP)** Ventilating Valves shall be Georg Fischer type 595. Dimensions DN10-100 are with pressure rating PN10. They shall be equipped with plastic coated stainless steel spring with minimal opening pressure (10-80 mbar).

- System Specification -

7. Welding and Assembly

All butt fusion fittings and valves shall also be manufactured with laying lengths designed for use with fusion machines IR-63 Plus, IR-110 Plus and IR-225 Plus from Georg Fischer Piping Systems, providing welds with increased mechanical and chemical stability than conventional welding methods (socket- and butt fusion).

The IR Plus fusion machines use non-contact radiant heating. The cooling time for is calculated on the basis of ambient temperature and the bead surface temperature. To increase the cooling capacity, an additional cooling fan is included in the IR-225 Plus.

Only authorised welders by Georg Fischer Piping Systems are allowed to perform fusion on the IR Plus machines.

As an alternative to IR fusion, conventional butt fusion according to DVS 2207-11 may be used, preferably with automated CNC controllers and weld recorders.

Socket fittings require the use of Socket Fusion welding tools according to DVS 2007-11, with heating bushes System B.

The welding and the installation should be in accordance with Georg Fischer Piping Systems guidelines.

- System Specification -**8. Measurement & Control / Instrumentation**

The following parameters can be measured (Sensors), indicated and/ or transmitted (transmitters) to PLC, PC and other Data Acquisition Systems. All products comply with the CE standard.

Parameter	Technology	Compatible liquids (*)
Flow	Paddlewheel	clean liquids
	Rotameter	clean liquids
	Magmeter	contaminated liquids
Level	Hydrostatic	all liquids
pH-ORP	Glas electrodes	all liquids
Conductivity	Contact	all liquids
Pressure	Piezoresistive	all liquids
Temperature	Pt1000	all liquids

(*) please check first the sensors limitations in material, pressure and temperature (data sheet) and chemical resistance list

8.1 Sensors

The sensors listed hereafter will transfer the measured value to a Georg Fischer Piping Systems Transmitter, to indicate the measured value and allowing simple calibration and maintenance of the devices. Alternatively the measured values of the sensors can be sent directly to a PLC, PC or other local made electronics using either an analogue signal (4-20mA, open collector or sinusoidal voltage) or a digital signal called S3L (Georg Fischer Piping Systems Signet serial signal).

8.1.1 Installation Fittings

Depending on the sensor type, special installation fittings shall be used for connection to the pipeline: Installation T-Fitting sizes d20-63 mm with double true union in PP, Wafer fitting on saddle sizes d75 – 315 mm and weld-outlet sizes d75 – d630 mm with as supplied by Georg Fischer Piping Systems. Sensor thread connection shall be 1¼" NPSM.

8.1.2 Flow sensors**8.1.2.1 Paddlewheel sensors****515 and 525 sensors:**

All sensors of this family are "sinusoidal" sensors. This sensor from Georg Fischer Piping Systems SIGNET requires no external power source to produce a signal. Internal to the body of the sensor is a wire coil which when excited by the rotor

- System Specification -

assembly produces a small sinusoidal signal. The rotor assembly consists of four paddles; inserted into each of the paddles of the rotor are magnets. As liquid flows past the rotor assembly it rotates each of the four paddles produces a sine wave signal as it passes the centre of the body (two paddles of the rotor produces a full AC sine wave). The sensors as manufactured by Georg Fischer Piping Systems SIGNET produce a signal output which is proportional to the flow rate. A K-factor (number of pulses generated by the sensor per 1 liter or 1 gallon of fluid the sensor) is used to define the size of the pipe that the sensor is inserted into.

3-2536 and 3-2537 sensors:

All sensors of this family of sensors are “Hall Effect” sensors. Internal to the Georg Fischer Piping Systems SIGNET sensors body is an open collector relay. The sensor is supplied with a voltage from the 3-8550 transmitters or an external power supply ranging from 5 to 24 volts. This voltage is switched through the open collector relay as the paddlewheel (rotor) of the sensor rotates. The sensor’s rotor assembly has four paddles. Inserted in two of the paddles is a magnet. As the paddles pass the centre of the sensors body, the magnetic field switches the open collector relay on and off which generates a square wave pulse as manufactured by Georg Fischer Piping Systems SIGNET. Two pulses indicates a complete rotation (on/off cycle) of the open collector relay. The pulse output is directly proportional to the fluid velocity. A K-factor (number of pulses generated by the sensor per 1 liter or 1 gallon of fluid passing the sensor) is used to define the size of the pipe that the sensor is inserted into.

8.1.2.2 Rotameters

As supplied by Georg Fischer Piping Systems are radially installed dismountable meters for flow rate measuring in industrial piping applications. If needed, minimum or maximum flow can also be monitored via limit switches. Also, analogue flow measurement with a 4...20mA Signal is possible.

The working principle of the rotameter is based in gravity and equilibrium of forces. If a medium flows upwards at a sufficient flow rate through the vertically mounted taper tube, the float is raised to the point at which a state of equilibrium sets in between the lifting force of the medium and the weight of the float. Since the mean rate of flow is proportional to the quantity flowing through per unit of time, this state of equilibrium corresponds to the measurement of the instantaneous flow rate.

Following types and sizes are available:

- Type SK, DN 10 – 65 mm
- Type 335, DN 25 – 65 mm
- Type 350, DN 25 – 65 mm

- System Specification -

8.1.2.3 Magmeter

The Magmeter sensor from Georg Fischer Piping Systems SIGNET consists of two metallic pins that produce a small magnetic field across the inside of the pipe. The The Magmeter measures the velocity of a conductive liquid (20 μ S or greater) as it moves across the magnetic field produced by the Magmeter. A voltage occurs on the sensor tips, which is directly proportional to the flow rate of the fluid. The magnetic signal is conditioned and translated in to a pulse signal. A K-factor (number of pulses generated by the sensor per 1 liter or 1 gallon of fluid passing the sensor) is used to define the size of the pipe that the sensor is inserted into. The Magmeter of Georg Fischer Piping Systems SIGNET is offered as a blind frequency, 4-20 mA or digital S3L output, or with integral display and control relays.

8.1.3 Level Sensor (hydrostatic level)

Hydrostatic pressure is the pressure exerted on a column of fluid by the weight of the fluid above it. Internal to the Georg Fischer Piping Systems SINGET PVDF sensor body is a ceramic diaphragm sensor and capillary tube/cable assembly. The ceramic diaphragm sensor exposed to the fluid senses the hydrostatic pressure of the fluid and compares the pressure to the atmospheric pressure monitored the capillary tube/cable assembly. The hydrostatic level sensor from Georg Fischer Piping Systems SIGNET only senses the hydrostatic pressure of the fluid. The Level Sensor is offered as a blind output 4-20mA or digital S3L output connected to the Georg Fischer Piping Systems SIGNET Transmitter unit.

8.1.4 pH Sensors

All pH sensors from Georg Fischer Piping Systems SIGNET are constructed commonly called combination electrodes. The measuring cell is constructed of hydrogen sensitive glass that can detect the concentration of hydrogen ions (+H) in a solution. The concentration of +H ions directly determines the pH of the fluid. The reference cell is used to provide a stable reference signal. The pH signal is measured against the stable reference signal. The reference junction allows the reference cell to come in contact with the fluid being measured. The measured signals are then conditioned and sent as a blind 4-20mA or as a digital S3L signal to the Georg Fischer Piping Systems SIGNET Transmitter unit.

8.1.5 ORP Sensors

All ORP sensors from Georg Fischer Piping Systems SIGNET are constructed similar to the pH sensors, except that a noble metal like platinum or gold replaces the silver chloride element of the measuring and reference cell of the pH electrode. Temperature compensation is not used in ORP measurements as well.

- System Specification -

ORP is an abbreviation for Oxidation-Reduction Potential. Oxidation is a term used to denote the occurrence of a molecule losing an electron. Reduction occurs as a molecule gains an electron. The “potential” is simply an indication of a solution’s propensity to contribute or accept electrons. ORP reactions (sometimes referred to as REDOX) always take place simultaneously. There is never oxidation without reduction, and ORP electrodes are used to detect electrons exchanged by molecules as these reactions occur.

The measured signals are then conditioned and sent as a blind 4-20mA or as a digital S3L signal to the Georg Fischer Piping Systems SIGNET Transmitter unit.

8.1.6 Conductivity Sensors

All Conductivity sensors from Georg Fischer Piping Systems SIGNET are manufactured using two stainless steel electrodes. Alternative materials are available in case of chemical incompatibility. Conductivity sensors measure the ability of a fluid to conduct an electrical current between two electrodes. The proper term for this ability of a solution is electrolytic conductivity, since only ions conduct electric current in solution. Electrolytic conductivity (or simply conductivity) is therefore an indirect measure of the ionic concentration of a solution. Generally, conductivity increases and decreases with the concentration of ions.

Most conductivity electrodes consist of two measuring half-cells. The geometry of the half-cells can be tailored to provide highly accurate measurements over a specific conductivity range. Cell constants help to describe electrode geometry for the purpose of selecting the appropriate electrode for a given application. A cell constant is defined as the length between the two halfcells divided by the area of the cells. All conductivity sensors have a temperature compensation circuits in order to increase the sensors accuracy.

The measured signals are then conditioned and sent as a blind 4-20mA or as a digital S3L signal to the Georg Fischer Piping Systems SIGNET Transmitter unit.

8.2 Transmitters

The Georg Fischer Piping Systems Signet 9900 Transmitter provides a single channel interface for many different parameters including Flow, pH/ORP, Conductivity/Resistivity, Salinity, Pressure, Temperature, Level and other sensors that output a 4 to 20 mA signal. The display shows separate lines for units, main and secondary measurements as well as a dial-type digital bar graph.

The 9900 is offered in both panel or field mount versions. Both configurations can run on 12 to 32 VDC power (24 VDC nominal). The 9900 can also be loop powered with compatible sensors.

- System Specification -

Designed for complete flexibility, plug-in modules allow the unit to easily adapt to meet changing customer needs. Optional modules include Relay, Direct Conductivity/Resistivity, H COMM and a PC COMM configuration tool.

- 1 sensor input (Flow, pH/ORP, Conductivity/Resistivity, Salinity, Pressure, Temperature, Level and other sensors that output a 4 to 20 mA signal, Signet 8058 i-Go™ Signal Converter required)
- 1 analogue output (4-20 mA)
- 1 Open Collector output
- Optional relay module with 2 Dry Contact Relay SPDT
- Power supply 12-32 VDC

The Georg Fischer Piping Systems Signet 8900 Multi-Parameter Controller takes the concept of modularity. Each 8900 is field commissioned with the users specified combination of inputs, outputs, and relays using simple-to-install modular boards into the base unit. Configure the system by selecting either two, four, or six input channels which accepts any of the Signet sensors listed below, and/or other manufacturer's sensors via a 4 to 20mA signal converter (Signet Model 8058). To complete your unit, choose a power module with universal AC line voltage or 12 to 24 VDC.

Analog output and relay modules are available and easily installed.

Derived measurements include difference, sum, ratio, percent recovery, percent rejection, percent passage and BTU. The menu system can be programmed to display in multi-languages including English, German, French, Spanish, Italian, and Portuguese.

- 2,4 or 6 sensor input (Flow, Level, pH-ORP, Conductivity, Pressure Temperature)
- 0,2 or 4 analogue output (4-20 mA or 0-10 Volts)
- 0,2,4,6 or 8 relay output
- Power supply 12-30 VDC or 110-230 VAC

8.3 Batch Control

A batch controller manufactured by +GF Signet Type 5600 allows batching a pre-selected quantity of liquid. After selection of the quantity to be dosed, a start signal (local or remote) will close a batch controller contact to energize or de-energize a valve and/or switch on a pump. The batch controller count the pulses coming from any Signet sensor with frequency output and stop the batch process as the pre-selected quantity is reached. Advanced

features include a user-set security code, an automatic calibration option, and overrun compensation The batch process is repeatable and is designed for intensive industrial applications.

- System Specification -

9. Quality

9.1 Production Conditions

Pipes, fittings, valves and accessories shall be manufactured in an environment operating a Quality Assurance System to ISO 9001 and an Environmental Management System conform to ISO 14001.

9.2 Marking

All components are embossed with a permanent identification during the production process to ensure full traceability. The following information will be mentioned:

- Manufacturer's name or trade mark
- Production lot number
- Material
- Dimension
- Pressure rating

9.3 Uniformity

Pipes, fittings, valves and Fusion IR Plus machines shall be supplied from one manufacturer, namely Georg Fischer Piping Systems to ensure correct and proper joining between components and uniform chemical and physical properties of the piping system.

9.4 CAD Library

All components shall be available in an online CAD library.

9.5 Training, Certification and Installation

Site personnel, involved with **PROGEF Standard (PP)** piping installation, shall undergo training and certification from an authorised local institution prior to performing any joining operations on site. For further information and training please contact Georg Fischer support under

Contact:

Georg Fischer Piping Systems Ltd.

Phone: +41 52 631 11 11

E-mail: info.ps@georgfischer.com