TECHNICAL DATASHEET



COMMERCIALOPAC THERMOSTATIC EXPOSED SHOWER VALVE WITH CHROME LEVER

Product Specification

Product Code: OP TS1503 EL C

Finish: Chrome Product Type: Commercial

Construction: Body is of brass construction and

is designed to conform to BS EN 1111:1999 (HP)

& BS EN 1287:1999 (LP)

Valve Type: Thermostatic Cartridge

Supply: Suitable for all plumbing systems (Preferably balanced)


Inlet Connections: 15mm compression elbows


Outlet Connections: 1/2" BSP

Working Pressures: Min 0.2bar, Max 8.0bar

Maximum Static Pressure: 10.0 bar

Dimensions for Fitting: 148-158mm inlet centres






Additional Information

- Single sequential control for both temperature & flow.
- Automatic thermostatic shut-off in the event of hot or cold water failure.
- Check valves and serviceable filters as standard
- Supplied as 'valve only' and thus can be customised by choosing accessories from our Pick 'N' Mix showering options. Please see our Product and Price guide for details.
- Adjustable inlet centres between 148-158mm.
- Chrome plated to BS EN 248.

Technical Advice: For further information please call 0844 7016273 or

email customercare@bristan.com

Guarantee: 1 year covering manufacturing faults.



Compliance / Approvals

WRAS: Certificate N°: 0712092

TMV3: Certificate N°: BC397/1208

Flow Rates (litres per minute)

System Pressure	0.2 bar	0.6 bar	1bar	2 bar	3 bar	4 bar	5 bar
Open Outlet	12.0	22.0	29.0	42.0	52.0	60.0	66.0











D2

The information contained on this page was correct at date of issue. Fitting dimensions are provided as a guide only. Some variation may occur due to manufacturing tolerances. Bristan pursues a policy of continuing improvement in design and performance of its products and so reserves the right to change specifications without prior notice.