# **TECHNICAL DATASHEET**



## COMMERCIAL OPAC THERMOSTATIC CONCEALED SHOWER VALVE WITH CHROME HANDWHEEL

### **Product** Specification

Product Code: OP TS1503 CH C

Finish: Chrome **Product Type:** Commercial

Construction: Body is of brass construction and

is designed to conform to BS EN 1111:1999 (HP)

& BS EN 1287:1999 (LP) Thermostatic Cartridge

Valve Type: Suitable for all plumbing systems (Preferably balanced) Supply:


Inlet Connections: 15mm compression elbows

**Outlet Connections:** 1/2" BSP

Working Pressures: Min 0.2bar. Max 8.0bar

Maximum Static Pressure: 10.0 bar

Dimensions for Fitting: 130mm inlet centres



### **Additional** Information

- Single sequential control for both temperature & flow.
- Anti-vandal stainless steel concealing plate
- Automatic thermostatic shut-off in the event of hot or cold water failure.
- Check valves and serviceable filters as standard
- Supplied as 'valve only' and thus can be customised by choosing accessories from our Pick 'N' Mix showering options. Please see our Product and Price auide for details.
- Inlet centres of 130mm +/- 1mm.
- Chrome plated to BS EN 248.

Technical Advice: For further information please call 0844 7016273 or

email customercare@bristan.com

Guarantee: 1 year covering manufacturing faults.

### Compliance / Approvals

WRAS: Certificate No: 0712092 TMV3. Certificate No. BC397/1208

Flow Rates (litres per minute)

<b>System</b> Pressure	<b>0.2</b> bar	<b>0.5</b> bar	1bar	<b>2</b> bar	<b>3</b> bar	<b>4</b> bar	<b>5</b> bar
Flow Limiters Fitted	4.6	6.8	7.1	8.1	8.6	8.9	9.0











