


t +44 (0) 23 8066 9666 f +44 (0) 23 8066 9606 sales@johnsonvalves.com www.johnsonvalves.com Data Sheet 14.07 01/10



PRESSURE REDUCING VALVES



BAILEY BIRKETT PRESSURE REDUCING VALVE



Part No. G4-2042 BRONZE BODY WITH BSP THREADED CONNECTIONS SUITABLE FOR STEAM

The G4 series of pilot operated pressure reducing valves provide extremely accurate levels of pressure regulation for steam, air and industrial gas applications. This is accomplished with a highly sensitive pilot which continuously monitors both inlet and outlet pressure simultaneously. The result is a constant outlet pressure, irrespective of erratic inlet pressure or system demand.

The valve relies upon a stable pressure signal from the outlet pipework in order to maintain stable control of the outlet pressure. However, under certain operating conditions the signal pressure may be unstable in the immediate vicinity of the valve outlet and as a result may cause erratic control. This can be easily overcome by installing a balance pipe.

All G4 valves can be remotely controlled where necessary by connecting a balance pipe from the remote control port and into the outlet pipework at a point where stable pressures are likely to occur.

This valve should be installed in a horizontal position.

When ordering, please state which pressure adjustment spring range is required for the downstream pressure.

Yellow Spring	0.35 - 3.5 Bar
Black Spring	0.7 - 7.0 Bar
White Spring	2.8 - 10.5 Bar
Green Spring	3.5 - 14.0 Bar
Red Spring	7.0 - 21.0 Bar

MATERIALS				
Body	Bronze			
Main Valve Trim	Stainless Steel			
Pilot Top	Bronze			

SIZE	DN15	DN20	DN25	DN32	DN40	DN50
Α	105	105	114	124	133	162
В	60	64	67	76	79	83
С	203	210	213	244	251	260

Features & Benefits

- Pilot operated.
- Compact design.
- Constant outlet pressure.
- Very high flow rates.
- Positive shut-off.

Pressure & Temperature

Maximum Inlet Pressure:-25 bar.

Reduced Pressure range:-

0.35 to 21 bar. (0.07 to 0.35 bar when fitted with low pressure top)

Temperature Range:-

225°C @ 25 bar. 260°C @ 17 bar.

AVAILABLE SPARES

Routine Service Pack.

Containing:-

Diaphragm, set of piston rings, pilot valve cap & set of joints.

Complete Repair Kit.

Containing:-

Diaphragm, set of piston rings, pilot valve assembly, main valve, main valve seat, main valve spring & set of joints.

Other Materials Available (Pressure & Temperature Data Differs)

Nitrile (GN), Viton (GV) & PTFE (GP) Valve Trim

For latest prices and delivery to your door visit MyTub Ltd - 0845 303 8383 - www.mytub.co.uk - info@mytub.co.uk