# **TECHNICAL**DATASHEET



#### **SENTINEL**

### MONOBLOC SINK MIXER

### **Product**Specification

**Product Code:** ST SNK C / ST SNK BN

**Finishes:** Chrome / Brushed Nickel

**Product Type:** Traditional

**Construction:** Body is of brass construction

and is designed to conform to BS EN 200


Valve Type: ½" turn ½" ceramic disc valves

**Supply:** Suitable for all plumbing systems, ideally balanced

**Inlet Connections:** M12 x 15mm screw-in copper inlet pipes

Water Pressure: Min. 0.2 bar, Max. 8.0 bar





#### **Additional**Information

- Dual flow
- · Incorporates swivel spout
- Chrome plated to BS EN 248

**Technical Advice:** For further information please call 0844 7016273 or email customercare@bristan.com.

**Guarantee:** 5 years covering manufacturing faults. Special effect finishes are covered by

a 3-yearguarantee

## Compliance/Approvals

WRAS: Certificate No. 0705059

FlowRates (litres per minute)

<b>System</b> Pressure	<b>0.5</b> bar	<b>1</b> bar	<b>2</b> bar	<b>3</b> bar	<b>5</b> bar
ST SNK (*) Mixed	12.37	17.65	25.16	31.87	41.14



