ST 35 / 40 / 50 / 90 / 130 Oil Burner

ST Oil Burner features:

- Energy saving and compatible with environmental requirements
- Quiet in operation and designed for easy maintenance
- Reliable and trouble-free
- Designed and approved in accordance with the European Standard EN 267
- Air snorkel available as optional extra
- Industry standard components easily available
- Single stage operation
- All kW ratings are nett CV

For more information on all Nu-way products please visit **www.nu-way.co.uk**

NU-WAY®
Enertech Group

For latest prices and delivery to your door visit MyTub Ltd - 0845 303 8383 - www.mytub.co.uk - info@mytub.co.uk

Type		ST 35	ST 40	ST 50	ST 90	ST 130
Capacity	**kW**	**14-28**	**18-39**	**24-66**	**47-119**	**59-158**
Motor	V/Hz	230/50	230/50	230/50	230/50	230/50
	W / A (Fuse)	90/6	90/6	90/6	125/6	125/6
Start / Run Current	Amps	3.5 / 0.77			2.5 / 0.95	
Control box		Satronic / Landis & Staefa				
Fuel pump		Danfoss				
Single Stage operation		•	•	•	•	•
Gross weight	kg	11	11	11	13	13
Volume	m^3	0.04	0.04	0.04	0.05	0.05













Burner	øA	B	C	D	E	F	G	H	I	K	L
ST 35	89	63	188	162	54	239	275	145	10.3	4	125-150
ST 40	89	63	188	162	54	239	275	145	10.3	4	125-150
ST 50	89	76	194	169	54	229	275	148	10.3	4	125-150
ST 90	89	80	237	200	54	258	295	158	10.3	4	125-150
ST 130	109	140	237	200	54	258	295	158	10.3	4	145-170

Enertech Limited, P O Box 1, Vines Lane
Droitwich, Worcestershire, WR9 8NA

tel: +44 (0) 1905 794331 • **fax:**+44 (0) 1905 794017
email: info@nu-way.co.uk • **web:** www.nu-way.co.uk

NU-WAY
Enertech Group

Issue 1 6/10

For latest prices and delivery to your door visit MyTub Ltd - 0845 303 8383 - www.mytub.co.uk - info@mytub.co.uk