



PB52HU Chromium Plated Hose Union Ball Type Bibtap







	DIMENSIONS (mm)						
23	Code	Description	А	В	С	D	Kg
	262021	1/2 PB52HU	88	45	45	105	0.28
	262022	3/4 PB52HU	88	45	50	105	0.36

PB52HU Chro Ball Type Bib	mium Plated Hose Union tap	Minimum Operating Pressure (bar)	g Maximum Cold Working Pressure (bar)	Maximum Hot Working Pressure (bar)				
1/2 PB52HU B/ BLACK LVR	ALLVALVE BTAP CAST	No Minimum Operating Pressure	16.0 bar at temperatures up to 60oC	8.0 bar at temperatures u to 100oC				
MATERIAL S	PECIFICATIONS							
Number	Component	N	Material					
1	Body	N	MS58 Brass					
2	Сар	N	/IS58 Brass					
3	Ball	Ball		MS58 Brass, Chrome Plated				
4	Ball Seal	F	TFE					
5	Spindle	N	IS58 Brass					
6	Spindle Seal	Ν	NBR					
7	Hose Pipe	N	MS58 Brass					
8	Hose Nut	Ν	MS58 Brass					
9	Hose Union O Ring	Ν	NBR					
10	Lever Securing Screw	Lever Securing Screw		Brass, Chromium Plated				
11	Lever	C	Cast Aluminium, Painted Black					
12	Gland Nut	N	MS58 Brass					
13	Flow Straightener	F	Polyethylene					

CARE & MAINTENANCE

Care

No regular aesthetic care is required for this product

Maintenance

A regular maintenance program is the most efficient method of ensuring longer term operational efficiency of the selected valve. Such a program would need to include a risk assessment and a planned procedure of how the maintenance will be carried out. The possibility of operational limits being exceeded and the potential hazards ensuring must be considered as part of this assessment. This should be implemented to include visual checks on the valve's condition and any development of unforeseen conditions, which could lead to failure. The correct fitting tools and equipment should be used for valve maintenance work. Separate means of draining the pipe work must be provided when carrying out any maintenance to valves. Where there may be any system debris this could be collected and /or filtered by installation of the appropriate protective device.

For further help please contact your local engineer.

If your product is under warranty please contact the Service Support Team on: 0800 1560050

GUARANTEE

Valves and Fittings

Pegler Yorkshire Customcare 5 Year Guarantee - Terms and Conditions

Products are subject to a 5 year guarantee that is between Pegler Yorkshire and the final purchaser of the product.

The guarantee is subject to proof of purchase being supplied.

This guarantee does not affect any statutory rights the consumer may have in law.

The guarantee covers manufacturing or material defects and does not cover parts subject to normal wear and tear.

This product range has been designed for the use of homeowners, domestic and commercial applications and therefore the guarantee is subject to the product being properly selected for their intended service conditions.

The guarantee is not applicable where the product is fitted contrary to the conditions in the fitting instructions.

This is reinforced where valves are covered by the European Pressure Equipment Directive (PED97/23/EC) where Installation, Operating and Maintenance Instructions are supplied with each product and/or carton.

Provided it is installed correctly and receives adequate preventative maintenance it should give years of trouble – free service.

Abusive behaviour and accidental damage to the product are not covered by this guarantee.

The extent of this liability is limited to the cost of the replacement of the defective item and not to fitting or consequential damages.