




Male elbow. copper x BSP taper male thread.

GENERAL INFORMATION

Size	Pattern No.	Box Qty	Code	Barcode	Price (£) ex VAT
12mm x 3/8	N13/4092G	10	84535	8022050845351	POA
12mm x 1/2	N13/4092G	10	84536	5022050845368	POA
15mm x 1/4"	N13/4092G	10	88495	5022050884954	£1814.96
15mm x 3/8	N13/4092G	10	84539	5022050845399	POA
15mm x 1/2"	N13/4092G	10	88497	5022050884978	£1195.00
15mm x 3/4	N13/4092G	10	84541	5022050845412	POA
18mm x 1/2	N13/4092G	10	84543	5022050845436	POA
18mm x 3/4	N13/4092G	10	84544	5022050845443	POA
22mm x 3/4"	N13/4092G	10	88505	5022050885050	£1684.78
22mm x 1	N13/4092G	10	84547	5022050845474	POA
28mm x 3/4	N13/4092G	10	84548	5022050845481	POA
28mm x 1"	N13/4092G	10	88509	5022050885098	£2383.61
35mm x 1 1/4"	N13/4092G	1	88510	5022050885104	£3827.27
42mm x 1 1/2"	N13/4092G	1	88511	5022050885111	£4552.39
54mm x 2"	N13/4092G	1	88512	5022050885128	£8049.10

DIMENSIONS (mm)



Code	Description	a	c	Za
84535	12mm x 3/8 N13/4092G	15	24	6
84536	12mm x 1/2 N13/4092G	16	28	7
88495	15mm x 1/4" N13/4092G	17	27	6
84539	15mm x 3/8 N13/4092G	17	23	6
88497	15mm x 1/2" N13/4092G	20	33	9
84541	15mm x 3/4 N13/4092G	22	29	11
84543	18mm x 1/2 N13/4092G	22	30	9
84544	18mm x 3/4 N13/4092G	25	31	12
88505	22mm x 3/4" N13/4092G	27	34	11
84547	22mm x 1 N13/4092G	30	38	14
84548	28mm x 3/4 N13/4092G	30	39	11
88509	28mm x 1" N13/4092G	34	38	15
88510	35mm x 1 1/4" N13/4092G	45	50	21
88511	42mm x 1 1/2" N13/4092G	48	52	20
88512	54mm x 2" N13/4092G	60	60	27

PRESSURE & TEMPERATURE

Endex (and Endbraz 67mm) performance when correctly assembled with copper tube to BS EN 1057 using tin/copper soft solder BS EN 29453 S-Sn99Cu1 or tin/silver soft solder BS EN 29453 L-SnAg5 DIN 1707

Service temperature

Size	-40 °C (Min)	30 °C	65 °C	110 °C (Max)
6mm to 28mm	25bar	25bar	25bar	16bar
35mm to 54mm	25bar	25bar	16bar	10bar
67mm	16bar	16bar	16bar	10bar

Endex (and Endbraz 67mm) performance when correctly assembled with copper tube to BS EN 1057 using tin/lead soft solder BS EN 29453 D-Pb60Sn40

Not suitable for use in potable water systems

Service temperature

Size	-15 °C (Min)	30 °C	65 °C	110 °C (Max)
6mm to 54mm	16bar	16bar	10bar	6bar
67mm	10bar	10bar	6bar	4bar

GUARANTEE

Pegler Yorkshire 25 Year Guarantee - Terms and Conditions

Products are subject to a 25 year guarantee that is between Pegler Yorkshire and the final purchaser of the product.

The guarantee is subject to proof of purchase being supplied.

This guarantee does not affect any statutory rights the consumer may have in law.

The guarantee covers manufacturing or material defects when installed in accordance with our instructions on specified tube materials and applications, and does not cover parts subject to normal wear and tear.

This product range has been designed for the use of homeowners, domestic and commercial applications and therefore the Guarantee is subject to the product being properly selected for their intended service conditions.

The guarantee is not applicable where the product is fitted contrary to the conditions in the fitting instructions.

This is reinforced where valves are covered by the European Pressure Equipment Directive (PED97/23/EC) where Installation, Operating and Maintenance Instructions are supplied with each product and/or carton.

Provided it is installed correctly and receives adequate preventative maintenance it should give years of trouble-free service.

Abusive behaviour and accidental damage to the product are not covered by this guarantee.

The extent of this liability is limited to the cost of the replacement of the defective item and not to installation or consequential damages.

APPROVALS



[DVGW](#)



[BSI](#)



[Russia](#)



[KIWA Gastec](#)



[CSN](#)



[WRAS](#)



[KIWA](#)