



Calder Washing Trough, 120cm Central Outlet Domed 2in Waste Tapholes For 2 Mixers - NEW

Illustrated

- S2824** Calder stainless steel washing trough 120cm long 2 taphole positions, central outlet with 2" domed waste
- B8861** Avon 21 washbasin mixer 1 hole, self closing push button, variable temperature with copper tube inlets
- A5900** TMV Thermostatic mixing valve 15mm

Configuration options

- A4169** Contour 21 washbasin mixer thermostatic 1 hole, single sequential long lever, copper tube inlet
- B8260** Piccolo 21 washbasin 1 taphole mixer, fitted 5 litres per minute aerated flow regulator, optional flow straightener, EasyFix, temperature limit stop, flexible tails no pop up waste



Weights

- S2824 10.00KG
- B8861 2.08KG

Standards

Stainless steel sheet to BS EN 10088:Part 2:2005

Colours

Stainless Steel (MY)

Special Notes

Consideration should be given to safe hot water delivery and the use of an appropriate temperature reduction device see A5900AA

Frequently used applications

- | | |
|--------------------|-----------------|
| Education | Factory |
| General Healthcare | Hotels |
| Office | Public Building |
| Pubs and Clubs | Retail |
| Sports and Leisure | Vandal Risk |

Accreditations

- WRAS
- Water Label

*Armitage
Shanks*

Tel: 0870 122 8822
Fax: 0870 122 8282
Email: info@idealspec.co.uk
Web: www.idealspec.co.uk

Ideal Standard (UK) Ltd. makes every effort to ensure that the information provided on its website is accurate. However, we cannot guarantee this, and accept no liability for any information or advice given via its website.

Powered by
IdealSpec

Date created:07/06/2013